

rev\_1



**WARRANTY**  
Passive Speakers: 5 Years  
Electronics & Powered Speakers: 3 Years

**Erikson**  
**AUDIO**

Effective March 1, 2017 / En vigueur le 1 mars, 2017  
Replaces October 1, 2016 / Remplace le 24 février, 2016

Suggested Retail Price List

	UPC	Sugg. Retail		UPC	Sugg. Retail
<b>Passive Speakers</b>					
<b>Sigma Series - Passive</b>					
<p>Introducing our exciting new passive series specifically engineered for fixed indoor installations and touring markets. With their discreet and unobtrusive design the SIGMA SERIES feature the latest proprietary Wharfedale Pro driver technology. In addition SIGMA SERIES use a newly developed angled corner port system so that the dimensions have been reduced without compromising the overall sound quality. Available in black or white and with comprehensive rigging options the new SIGMA SERIES is set to become a versatile and favourite choice for installers.</p>					
<b>Sigma8-BLK</b>	703341065409	360.00			
	Black 8 Passive 2-way 200W RMS				
<b>Sigma8-WHT</b>	703341120962	360.00			
	White 8 Passive 2-way 200W RMS				
<b>Sigma10-BLK</b>	703341065522	535.00			
	Black 10 Passive 2-way 300W RMS				
<b>Sigma10-WHT</b>	703341121082	535.00			
	White 10 Passive 2-way 300W RMS				
<b>Sigma12-BLK</b>	703341095888	605.00			
	Black 12 Passive 2-way 350W RMS				
<b>Sigma12-WHT</b>	703341121204	605.00			
	White 12 Passive 2-way 350W RMS				
<b>Sigma15-BLK</b>	703341065768	720.00			
	Black 15 Passive 2-way 400W RMS				
			<b>Sigma15-WHT</b>	703341121327	720.00
				White 15 Passive 2-way 400W RMS	
			<b>Sigma18B-BLK</b>	703341065881	795.00
				Black 18" Sub Passive 750W	
			<b>Sigma18B-WHT</b>	703341121440	795.00
				White 18" Sub Passive 750W	
			<b>Sigma V4-Black</b>	703341167042	430.00
				4x3" line array 300W program	
			<b>Sigma V4-White</b>	703341167165	430.00
				4x3" line array 300W program	
			<b>Sigma V8-Black</b>	703341167288	779.00
				8x3" line array 600W program	
			<b>Sigma V8-White</b>	703341167400	779.00
				8x3" line array 600W program	

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prix n'inclus pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com

Page 1.

**JAM**  
copyright © Jam Industries Ltd.

Suggested Retail Price List

UPC	Sugg. Retail	UPC	Sugg. Retail
-----	--------------	-----	--------------

## Impact Series - Passive

The IMPACT Series delivers extreme performance and power handling with unprecedented reliability and value. The series comprises of four models, IMPACT 15, 215, 18B and 218B. The strong wooden cabinets are covered in a textured black paint to give a durable yet stylish finish, which brings a professional look to any sound reinforcement environment. The IMPACT Series has a desirable high power capacity and clarity, as well as, an exceptional low frequency output providing tight bass all the way down to a 30Hz response. For high frequency, a 1.75" titanium-diaphragm compression driver produces a powerful yet neutral sounding high end. All IMPACT Series speakers use specially developed LF & HF drive units, which are designed in-house by our expert engineers and handmade in our own factory. Everything about the IMPACT Series screams 'Premium Product' except for the price tag, and we believe that you will find it impossible to find a better sounding loudspeaker for anywhere near this price point.

### Impact-15



703340979844 **345.00**  
2-way • 15" • FREQUENCY RESPONSE (±3DB): 50-18kHz • SENSITIVITY (1W @ 1M): 98dB • 1400W (PEAK); 700W (PROGRAMME); 350W (RMS) • NOMINAL IMPEDANCE: 8 ohms • MAX SPL: 130dB • NET WEIGHT: 22.8 Kg/ 50.16 lbs • DIMENSIONS (H/W/D): 680mm x 444.5/245.3mm x 429mm

### Impact-215











703340979967 **535.00**  
QUASI 3-way • 2 X 15" • FREQUENCY RESPONSE (±3DB): 45-18kHz • SENSITIVITY (1W @ 1M): 100dB • 800W (PEAK); 1400W (PROGRAMME); 700W (RMS) • NOMINAL IMPEDANCE: 4 ohms • MAX SPL: 135dB • NET WEIGHT: 34.5 Kg/ 75.9 lbs • DIMENSIONS (H/W/D): 1058mm x 444.5/245.3mm x 429mm

## Impact X Series - Passive

IMPACT-X IS A NEW COLLECTION OF PASSIVE ROAD-READY LOUDSPEAKERS SPECIFICALLY DESIGNED FOR HARDWORKING PERFORMERS. IMPACT-X is tough. The cabinets are protected by proprietary Rhino Rock paint which means these loudspeakers will look as good as new even after many successful tours, parties and events. Special attention has been paid to the port and port mouth to ensure a huge bass output with detail and minimized distortion. For the floor monitors the port mouth is parallel to the ground. This creates a reflective boundary which results in low end punch from a smaller cabinet. With 8 models in the passive range, this comprehensive lineup is easy to understand.



	<b>IMPACT-X12</b>	703341156008	<b>390.00</b>
		12" 2-way 600W programme 8ohm painted	
	<b>IMPACT-X12M</b>	703341156121	<b>390.00</b>
		12" 2-way wedge 600W programme 8ohm painted	
	<b>IMPACT-X15</b>	703341156244	<b>430.00</b>
		15" 2-way 700W programme 8ohm painted	
	<b>IMPACT-X15M</b>	703341156367	<b>430.00</b>
		15" 2-way wedge 700W programme 8ohm painted	
	<b>IMPACT-X215</b>	703341156480	<b>649.00</b>
		2x15" quasi 3-way 1400W programme 8ohm painted	
	<b>IMPACT-X15B</b>	703341156602	<b>505.00</b>
		15" sub 800W 4 ohm	
	<b>IMPACT-X18B</b>	703341156725	<b>575.00</b>
		18" sub 1000W 4 ohm	
	<b>IMPACT-X218B</b>	703341156848	<b>1155.00</b>
		2x18" Sub 2000W 8 ohm	

## Suggested Retail Price List

UPC	Sugg. Retail	UPC	Sugg. Retail
<b>EVP-X MKII Series - Passive</b>			
<b>The Evolution of the EVP-X MKII Series:</b> From the EVP, EVP-X and now the EVP-X MKII, Wharfedale Pro have honed one of the most well respected and reliable speaker series in the industry. Now in the era of the MKII, you can now put your trust into a demanding yet durable PA sound system, built around Wharfedale Pro's latest acoustic and manufacturing innovations. The new series serves up an extra 20% power handling and an additional 32dB SPL over the original EVP-X.			
<b>Key Features</b>			
<ul style="list-style-type: none"> <li>• 90 x 60 Elliptical Wave Guide Horn</li> <li>• 1.75" (44mm) titanium diaphragm drivers</li> <li>• ProTech™ Driver</li> <li>• +3dB HF Frequency boost switch (speakers)</li> <li>• Speakon and 6.3mm jack connections</li> <li>• Built in crossover (subwoofers)</li> <li>• Signal and Protect LEDs (speakers)</li> <li>• Durable black carpet covering</li> </ul>			
<b>EVP-X12MKII</b>	703340881321	<b>375.00</b>	
	2 way, 8 ohm, 55-20kHz(+/-3dB) • Power Rating: 300W Continuous, 600W Music, 1200W Peak • Product Dimension (H x W x D): (MM): 590 x 430/297.5 x 370; (inches): 23.20" x 16.90"/11.70" x 14.60" • Weight: 18.92kg/41.60lbs		
<b>EVP-X12MMKII</b>	703340881444	<b>375.00</b>	
	2 way monitor, 8 ohm • 60-20kHz(+/-3dB) • Power Rating: 300W Continuous, 600W Music, 1200W Peak • Product Dimension (H x W x D): (MM): 560 x 424 x 441; (inches): 22.00" x 16.70" x 17.40" • Weight: 17.96kg/39.50lbs		
<b>EVP-X15MKII</b>	703340881567	<b>405.00</b>	
	2 way, 8 ohm, 45-20kHz(+/-3dB) • Power Rating: 350W Continuous, 700W Music, 1400W Peak • Product Dimension (H x W x D): (MM): 675 x 460/294.5 x 450; (inches): 26.60" x 18.10"/11.50" x 17.70" • Weight: 23.92kg/52.60lbs		
<b>EVP-X15MMKII</b>	703340881925	<b>405.00</b>	
	2 way monitor • 8 ohm, 50-20kHz(+/-3dB) • Power Rating: 350W Continuous, 700W Music, 1400W Peak • Product Dimension (H x W x D): (MM): 645 x 445 x 473.5, (inches): 25.40" x 17.50" x 18.60" • Weight: 20.90kg/45.98lbs		
<b>EVP-X215MKII</b>	703340881802	<b>649.00</b>	
	Quasi 3 way, 4 ohm, 40-20kHz(+/-3dB) • Power Rating: 700W Continuous, 1400W Music, 2800W Peak • Product Dimension (H x W x D): (MM): 1058 x 502/330 x 467; (inches): 41.60" x 19.80"/13.00" x 18.40" • Weight: 41.28kg/90.80lbs		
<b>EVP-X15BMKII</b>	703340881925	<b>475.00</b>	
	15" subwoofer, 4 ohm, 40-250Hz (+/-3dB) • Power Rating: 400W Continuous, 800W Music, 1600W Peak • Product Dimension (H x W x D): (MM): 591 x 460 x 510; (inches): 23.20" x 18.10" x 20.00" • Weight: 28.06kg/61.70lbs		

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Le produit avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prix n'inclus pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com

Suggested Retail Price List

	UPC	Sugg. Retail		UPC	Sugg. Retail	
<b>EVP-X18BMKII</b>	703340882045	605.00		<b>Delta12</b>	703340600403	695.00
18" subwoofer, 4 ohm, 35-250Hz (+/-3dB) • Power Rating: 600W Continuous, 1200W Music, 2400W Peak • Product Dimension (H x W x D): (MM): 650 x 522 x 610; (inches): 15.50" x 20.60" x 24.00" • Weight: 39.30kg/86.50lbs				2-Way 12" High Power, Low Distortion Cast Frame Woofer • 1.4" Exit 2" Titanium Diaphragm Compression Driver • 90°x45° Elliptical Waveguide • Switchable Fullrange/Bi-amp Mode • Dual Angle Pole Mount Receptacle • Rhino Rock™ Textured Composite Finish • Plywood Construction • Rubberised 4-way Handles • POWER HANDLING (continuous/peak/programme): 400W/1600W/800W • FREQUENCY RESPONSE (+/- 3DB): 60-20KHz • SENSITIVITY: 97dB • NOMINAL IMPEDANCE: 8Ω • MAX SPL: 129dB • NET WEIGHT: 24.7Kg/ 54.5lbs • GROSS WEIGHT: 29.0Kg/ 63.8lbs • DIMENSIONS (h/w/d): 630mm / 24.8" X 390/241.2mm X 15.3/9.5" x 373mm / 14.7"		
<b>EVP-X218BMKII</b>	703340994243	1099.00		<b>Delta12M</b>	703340600526	695.00
2 x 18" Sub • Frequency Response 33 – 300 Hz • Power (RMS / Programme / Peak) 1200W / 2400W / 4800W • Nominal Impedance 4ohms • Sensitivity dB SPL @ 1W / 1M: 107 • Max dB SPL: 137 • Pole Mount 2 x 35mm Pole Socket • Input Connector 2 x Speakon and 2 x 1/4" • High pass filter connector output 1 x Speakon and 1 x 1/4" Jack • Net Weight 69kg / 152.12lbs • Product Dimensions: (mm) 650 x 610 x 1020				Angled stage monitor • 2-Way 12" High Power, Low Distortion Cast Frame Woofer • 1.4" Exit 2" Titanium Diaphragm Compression Driver • 90°x45° Elliptical Waveguide • Switchable Fullrange/Bi-amp Mode • Dual Angle Pole Mount Receptacle • Rhino Rock™ Textured Composite Finish • Plywood Construction • Rubberised 4-way Handles • POWER HANDLING (continuous/peak/programme): 400W/1600W/800W • FREQUENCY RESPONSE (+/- 3DB): 60-20KHz • SENSITIVITY: 97dB • NOMINAL IMPEDANCE: 8Ω • MAX SPL: 129dB • NET WEIGHT: 24.7Kg/ 54.5lbs • GROSS WEIGHT: 29.0Kg/ 63.8lbs • DIMENSIONS (h/w/d): 630mm / 24.8" x 390/241.2mm x 15.3/9.5" x 373mm / 14.7"		
<b>DELTA Series</b>						
<i>The Delta Series has been engineered from the ground up to provide outstanding performance and reliability. It utilises robust technology and durable components to ensure that it can meet the demands of touring, rental and fixed installation applications.</i>						
<i>High output, low distortion cast frame woofers with 3" voice coils are used throughout the range for unparalleled low frequency reproduction. 2" titanium compression drivers are coupled to 90°x45° elliptical waveguides for impressive output level and smooth HF dispersion.</i>						
<i>Comprehensive rigging points are provided on Delta 10, 12 and Delta 15 models, the Delta Series is equally at home in ground-stacked or flown applications. Rhino Rock™, our new texturised composite finish is used in all models. This new finish provides the great look of a painted finish with the durability of a carpet covered enclosure, giving you the best of both worlds. The Delta Series is constructed from plywood and features dual angle pole mounts to ensure that your sound is aimed directly at the audience, not at the ceiling.</i>						
<b>Delta10</b>	703340794201	579.00		<b>Delta15</b>	703340600649	820.00
2-Way 10" High Power, Low Distortion Cast Frame Woofer • 1.75" Exit 1" Titanium Diaphragm Compression Driver • 90°x60° Elliptical Waveguide • Switchable Fullrange/Bi-amp Mode • Dual Angle Pole Mount Receptacle • Rhino Rock™ Textured Composite Finish • Plywood Construction • Rubberised 4-way Handles • POWER HANDLING (continuous/peak/programme): 300W/1200W/600W • FREQUENCY RESPONSE (+/- 3DB): 65-20KHz • SENSITIVITY: 97dB • NOMINAL IMPEDANCE: 8Ω • MAX SPL: 128dB • NET WEIGHT: 16.58Kg/ 36.5lbs • GROSS WEIGHT: 19.6Kg/ 43.0lbs • DIMENSIONS (h/w/d): 500mm X 338/212.4mm x 330mm				2-Way 15" High Power, Low Distortion Cast Frame Woofer • 1.4" Exit 2" Titanium Diaphragm Compression Driver • 90°x45° Elliptical Waveguide • Switchable Fullrange/Bi-amp Mode • Dual Angle Pole Mount Receptacle • Rhino Rock™ Textured Composite Finish • Plywood Construction • Rubberised 4-way Handles • POWER HANDLING (continuous/peak/programme): 500W/2000W/1000W • FREQUENCY RESPONSE (+/- 3DB): 50-20KHz • SENSITIVITY: 98dB • NOMINAL IMPEDANCE: 8Ω • MAX SPL: 131dB • NET WEIGHT: 29.9Kg/ 65.9lbs • GROSS WEIGHT: 35.5Kg/ 78.1lbs • DIMENSIONS (h/w/d): 700mm / 27.6" X 446/281.4mm / 17.6/11.1" X 406mm / 16"		
				<b>Delta15M</b>	703340600762	820.00
				Angled stage monitor • 2-Way 15" High Power, Low Distortion Cast Frame Woofer • 1.4" Exit 2" Titanium Diaphragm Compression Driver • 90°x45° Elliptical Waveguide • Switchable Fullrange/Bi-amp Mode • Dual Angle Pole Mount Receptacle • Rhino Rock™ Textured Composite Finish • Plywood Construction • Rubberised 4-way Handles • POWER HANDLING (continuous/peak/programme): 500W/2000W/1000W • FREQUENCY RESPONSE (+/- 3DB): 50-20KHz • SENSITIVITY: 98dB • NOMINAL IMPEDANCE: 8Ω • MAX SPL: 131dB • NET WEIGHT: 27.24Kg/ 59.9lbs • GROSS WEIGHT: 33.96Kg/ 74.7lbs • DIMENSIONS (h/w/d): 493mm / 19.4" X 446mm / 17.6" / 17.6/11.1" X 685mm / 27"		

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prix n'inclut pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com



rev\_1



**WARRANTY**  
Passive Speakers: 5 Years  
Electronics & Powered Speakers: 3 Years

**Erikson**  
**AUDIO**

Effective March 1, 2017 / En vigueur le 1 mars, 2017  
Replaces October 1, 2016 / Remplace le 24 février, 2016

Suggested Retail Price List

	UPC	Sugg. Retail		UPC	Sugg. Retail
<b>Delta215</b>	703340600885	1229.00	 <p>Quasi 3-Way 2x15" High Power, Low Distortion Cast Frame Woofer • 1.4" Exit 2" Titanium Diaphragm Compression Driver • 90°x45° Elliptical Waveguide • Switchable Fullrange/Bi-amp Mode • Dual Angle Pole Mount Receptacle • Rhino Rock™ Textured Composite Finish • Plywood Construction • Rubberised 4-way Handles • POWER HANDLING (continuous/peak/programme): 1000W/4000W/2000W • FREQUENCY RESPONSE (+/- 3DB): 45-20KHz • SENSITIVITY: 101dB • NOMINAL IMPEDANCE: 4Ω • MAX SPL: 137dB • NET WEIGHT: 52.9Kg/ 116.6lbs • GROSS WEIGHT: 59.0Kg/ 130.0lbs • DIMENSIONS (h/w/d): 1135mm / 44.7" X 488/299.6mm / 19.2/11.8" X 450mm / 17.7"</p>		
<b>Delta15B</b>	703340601004	795.00	 <p>Subwoofer • 15" High Power, Low Distortion Cast Frame Woofer • Switchable Fullrange/Bi-amp Mode • Steel Pole Mount Receptacle • Rhino Rock™ Textured Composite Finish • Plywood Construction • Rubberised 4-way Handles • POWER HANDLING (continuous / peak/ programme): 700W/2800W/1400W • FREQUENCY RESPONSE (BI-AMP / PASSIVE) (+/- 3DB): 42-2KHz / 42-150Hz • SENSITIVITY: 98dB • NOMINAL IMPEDANCE: 8Ω • MAX SPL: 132dB • NET WEIGHT: 31.5Kg/ 69.4lbs • GROSS WEIGHT: 35.12Kg/ 77.4lbs • DIMENSIONS (h/w/d): 471mm / 18.5" X 471mm / 18.5" X 600mm / 23.6"</p>		
<b>Delta18B</b>	703340601127	969.00	 <p>Subwoofer • 18" High Power, Low Distortion Cast Frame Woofer • Switchable Fullrange/Bi-amp Mode • Steel Pole Mount Receptacle • Rhino Rock™ Textured Composite Finish • Plywood Construction • Rubberised 4-way Handles • POWER HANDLING (continuous/ peak/ programme): 800W/3200W/1600W • FREQUENCY RESPONSE (BI-AMP / PASSIVE) (+/- 3DB): 38-1.5KHz / 38-150Hz • SENSITIVITY: 99dB • NOMINAL IMPEDANCE: 8Ω • MAX SPL: 134dB • NET WEIGHT: 37.3Kg/ 82.06lbs • GROSS WEIGHT: 43.2Kg/ 95.04lbs • DIMENSIONS (h/w/d): 539mm / 21.2" X 539mm / 21.2" X 650mm / 25.6"</p>		
<b>Delta218B</b>	703340601240	1545.00	 <p>Dual Chamber Subwoofer • 2x18" High Power, Low Distortion Cast Frame Woofer • Switchable Fullrange/Bi-amp Mode • Steel Pole Mount Receptacle • Rhino Rock™ Textured Composite Finish • Plywood Construction • Rubberised 4-way Handles • POWER HANDLING (continuous/peak/programme): 800W/3200/1600 • FREQUENCY RESPONSE (BI-AMP) (+/- 3DB): 38-1.5KHz / 30-1.5KHz • SENSITIVITY: 100dB • NOMINAL IMPEDANCE: 8Ωx2 • MAX SPL: 138dB • NET WEIGHT: 78.9Kg/ 173.9lbs • GROSS WEIGHT: 86.0Kg/ 189.6lbs • DIMENSIONS (h/w/d): 541mm / 21.3" X 1041mm / 41" X 650mm / 25.6"</p>		

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prix n'inclus pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com

Page 5.

**JAM**  
copyright © Jam Industries Ltd.

Suggested Retail Price List

	UPC	Sugg. Retail	UPC	Sugg. Retail
--	-----	--------------	-----	--------------

## Focus Series

An exceptional point-source array system with a high level of performance and scalability. Exceptional clarity and extraordinary power handling un-rivaled in its class. New advanced driver technology, allowing Focus to reach extreme SPL levels while remaining musical. Intelligently constructed with a wide range of rigging points allowing you to fly in line-array configuration, independently, in pairs or stacked on top of subwoofers. Equipped with tour ready Wharfedale Pro components, Focus is ready to work night after night, simply put Focus series Pushes the boundaries of Point Source Systems, offering breakthrough levels of performance at an affordable price.

### Focus12

703340882168

1515.00



12" 2 way • Frequency Response (+/- 3dB): 60-20KHZ • Continuous / Programme/Peak: 500W/1000W/2000W • Nominal Impedance (ohms): 8 • Sensitivity: 99.5dB • Max SPL: 133dB • Nominal Coverage(H x V): 100°x10° • XOver: 1.6kHz • BiAmp Mode Switch • Rigging Points: M10X11&4 FlyTrack • Rigging Point Max Rated Weight: 500kg • Pole Mount: Dual-angle 35 mm pole socket • 2xSpeakon • Net Weight (kg / Lbs): 263/57.9 • Dimensions (H x W x D)mm: 625x455/270x435

### Focus15

703340882281

1730.00



System Type: 15" 2 way • Frequency Response (+/- 3dB): 50-20KHZ • Continuous/Programme/Peak: 700W/1400W/2800W • Nominal Impedance (ohms): 8 ohms • Sensitivity dB SPL @ 1W/1M: 99.5dB • Max SPL dB SPL @ Peak Rated Power: 135dB • Nominal Coverage @ 1kHz (H x V): 100°x10° • Crossover Frequency: 1.6kHz • BiAmp Mode Switch: YES • Rigging Points: M10X11&4FlyTrack • Rigging Point Max Rated Weight: 500kg • Pole Mount: DualAngle (0° or -10°) 35 mm pole socket • Input Connector Type: 2xSpeakon • Net Weight (kg / Lbs): 341/75 • Product Dimensions (H x W x D) mm: 690x445/224 5x433

### Focus18Sub

703340882403

1299.00



System Type: 18" Subwoofer • Frequency Response (+/- 3dB): 35-800HZ • Continuous/Programme/Peak: 1 tX)W/2000W/4000W • Nominal Impedance (ohms): 8 ohms • Sensitivity dB SPL @ 1W/1M: 104dB • Max SPL dB SPL @ Peak Rated Power: 140dB • BiAmp Mode Switch: NO • Pole Mount: M20 screw-on pole mount • Input Connector Type: 2xSpeakon • Net Weight (kg / Lbs): 52.4/115.3 • Product Dimensions (H x W x D)mm: 540x490x900

### Focus218Sub

703340882526

2165.00



System Type: Dual 18" Subwoofer • Frequency Response (+/- 3dB): 30-800HZ • Continuous/Programme/Peak: Parallel:2000W/4000W/8000W Discrete: 1000W/2000W/4000W • Nominal Impedance (ohms): Parallel 4 ohms Discrete: 2x8 ohms • Sensitivity dB SPL @ 1W/1M: 107dB • Max SPL dB SPL @ Peak Rated Power: 146dB • BiAmp Mode Switch: YES • Pole Mount: M20 screw-on pole mount • Input Connector Type: 2xSpeakon • Net Weight (kg / Lbs): 86,5/190.3 • Product Dimensions (H x W x D)mm: 540x880x900

Suggested Retail Price List

UPC	Sugg. Retail	UPC	Sugg. Retail
-----	--------------	-----	--------------

## Active Speakers

### Kinetic Series - Active

*Kinetic active series, like its passive counterpart, are suitable for a wide range of applications, making them ideal for portable DJ's and small brands where heavy duty sound reinforcement is a must within a budget price. Being self powered they are easy to use and install, yet do not compromise on any professional features. Using SMD (Surface Mount Devices) technology for Class D power amplifiers at both high and low frequencies, these active speakers offer low distortion and highly efficient performance. They are protected for thermal, DC and short circuit faults making them one of safest speakers in the market.*

#### Features

- Low Distortion, High Power Custom Wharfedale Pro Woofers, HF Compression Drivers
- 90°x60° Elliptical Waveguides
- High Slope Crossover With High Voltage Components
- PTC HF Driver Protection Circuitry
- Low Resonance Enclosures with **Road-Tough Black Carpet Finish**
- High-Impact Plastic Handles & Pole Mount Receptacles (Steel On Kinetic 153 & 18B)
- Parallel Speakon / " Jack Inputs
- High Pass Output (Kinetic 18B Only)
- Optional Brackets: WPB-2

#### Kinetic12A

703340740925

680.00



Active 12"2-way Bi-Amplified system • FREQUENCY RESPONSE ( $\pm 3$ DB): 60-20kHz • POWER Low Freq: 220W (CONTINUOUS); 350W (PEAK); Hi Freq.: 70W (CONTINUOUS); 140W (PEAK) • NOMINAL IMPEDANCE: 4 ohms • 2-Band EQ • NET WEIGHT: 13.26 Kg/ 29.2 lbs

#### Kinetic12MA

703340741762

795.00



Active 12"2-way Bi-Amplified system Angled Monitor • FREQUENCY RESPONSE ( $\pm 3$ DB): 60-20kHz • POWER Low Freq: 220W (CONTINUOUS); 350W (PEAK); Hi Freq.: 70W (CONTINUOUS); 140W (PEAK) • NOMINAL IMPEDANCE: 4 ohms • 2-Band EQ • NET WEIGHT: 13.26 Kg/ 29.2 lbs

#### Kinetic15A

703340742608

835.00



Active 15"2-way Bi-Amplified system • FREQUENCY RESPONSE ( $\pm 3$ DB): 50-20kHz • POWER Low Freq: 220W (CONTINUOUS); 350W (PEAK); Hi Freq.: 70W (CONTINUOUS); 140W (PEAK) • NOMINAL IMPEDANCE: 4 ohms • 2-Band EQ • NET WEIGHT: 18.7 Kg/ 41.14 lbs

#### Kinetic215A

703340743445

1099.00



2 x 15" active 2-way bi-amplified system • 400W RMS • 700W Peak • Class D LF and Class AB HF power amplifiers • LF and HF signal limiting • 1.2 inch (30.5mm) phenolic diaphragm compression driver • 90°x60° High Frequency Elliptical Wave Guide (EWG) • High power 2.5" voice coil subwoofer • Thermal, DC and short circuit fault protection • Bass/Treble EQ controls • Built in 2 channel TRS jack and male XLR balanced line level or MIC • level inputs • Female XLR balanced line level output • Rear panel LED • Volume control • Tear drop shaped handles • Covered in rugged black carpet • Net Weight: 29.42kg /64.7lbs

#### Kinetic18BA

703340744282

1010.00



18" Active reflex subwoofer • Power amplifier(Class D) • 300W RMS 600W peak • Preset integral peak limiter prevents signal distortion and amplifier clipping • Integral phase switch with 0°and 180°selections • Adjustable crossover frequency: 80Hz-200Hz • TRS Jack and male XLR balanced inputs on channel 2 • Female XLR balanced line level output • High pass filters the signal at 100Hz to the outputs • Integral pole mount adapter • Black carpet enclosure • Net Weight: 31.6kg /69.52lbs

Suggested Retail Price List

UPC	Sugg. Retail	UPC	Sugg. Retail
-----	--------------	-----	--------------

**Delta Series - Active**

Specifically designed as a multi purpose solution, Delta Active provides high end active sound reinforcement for touring applications and professional musicians. By combining legendary audio quality, renowned durability and affordability, Delta Active sets a new standard in the category of active loudspeakers. Capable of producing extraordinary levels of SPL and output, inside every Delta Active speaker is a high head room amplifier exclusively engineered by Wharfedale Pro. High Output low distortion woofers with 3 voice coils are used throughout the range for unparalleled frequency reproduction. 2" titanium compression drivers offer impressive output level and smooth HF dispersion. Delta Active 2 way speakers feature an integrated two channel mixer with onboard Qubit DSP insuring smoother more controlled sonic performance. In a world where some active speakers are found wanting, Delta Active delivers sound with substance.

**Delta18BA**



703340894161 **1849.00**  
18" Active subwoofer • Power amplifier(Class D) • 1000W• FREQUENCY RESPONSE (±3DB): 38Hz-200Hz • NOMINAL IMPEDANCE: 8 ohms • NET WEIGHT: 38.4 Kg/ 84.48 lbs • Dimensions (HxWxD) mm: 539x539x650

**Delta12A**



703340890569 **1299.00**  
Active 12" 2-way Bi-Amplified system • FREQUENCY RESPONSE (±3DB): 60 -20kHz • POWER Low Freq (Class D): 650W(80Hz); Hi Freq. (Class A/B): 100W(10kHz) • NOMINAL IMPEDANCE: 4 ohms • NET WEIGHT: 27.9 Kg/ 61.2 lbs • Dimensions (HxWxD) mm: 630x390/241.2x373

**Delta15A**



703340891405 **1515.00**  
Active 15" 2-way Bi-Amplified system • FREQUENCY RESPONSE (±3DB): 50 -20kHz • POWER Low Freq (Class D): 650W(80Hz); Hi Freq. (Class A/B): 100W(10kHz) • NOMINAL IMPEDANCE: 4 ohms • NET WEIGHT: 33.0 Kg/ 72.6 lbs • Dimensions (HxWxD) mm: 700x446/281.4x406

**Delta15BA**





703340893201 **1515.00**  
15" Active subwoofer • Power amplifier(Class D) • 900W• FREQUENCY RESPONSE (±3DB): 42Hz-200Hz • NOMINAL IMPEDANCE: 8 ohms • NET WEIGHT: 33.1 Kg/ 72.8 lbs • Dimensions (HxWxD) mm: 471x471x600

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.  
PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.  
Prix n'inclus pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.



## Suggested Retail Price List

	UPC	Sugg. Retail		UPC	Sugg. Retail
<b>Programme Series</b>					
<b>Programme35ET</b>	703340101283	420.00			
			2-Way, 6.5"high power woofer • 65-20kHz frequency response • 8 ohm • Continuous 60W / Music 120W / Peak 240W • 1" (25.4mm) Mylar Dome drive unit • Low distortion, high power woofer • High strength MDF cabinet • Pro-tech® (PTC) driver protection • Four (4) M6 hanging points • Parallel spring crimp input connectors • Universal Bracket Included		
<b>Programme105TBlack</b>	703340101405	305.00			
			2-Way, 5"high power woofer • 75-20kHz frequency response (+/-3dB) • 8 ohm • Continuous 80W / Music 160W / Peak 320W • 1" (25.4mm) Titanium Dome HF • Low distortion, high power woofers • High strength Trapezoidal cabinet • Pro-tech (PTC) driver protection • M8 High Strength Hanging Points • Barrier strip • Supplied with an Adjustable Heavy Duty Steel Wall Bracket.		
<b>Programme105TWhite</b>	703340101641	305.00			
			5" two way 80W Installation speaker • as above in White		
<b>Programme108TBlack</b>	703340103447	490.00			
			2-Way, 8"high power woofer • 60-20kHz frequency response (+/-3dB) • 8 ohm • Continuous 150W / Music 300W / Peak 600W • 1" (25.4mm) Titanium Compression Driver • Low distortion, high power woofers • High strength Trapezoidal cabinet • Pro-tech(Bulb) driver protection • M8 High Strength Hanging Points • Barrier strip • Supplied with an Adjustable Heavy Duty Steel Wall Bracket.		
<b>Programme108TWhite</b>	703340103560	490.00			
			8" Installation 150W Installation speaker • as above in White		
<b>Programme205TBlack</b>	703340102006	375.00			
			2-Way, 5"x2 high power woofer • 70-20kHz frequency response (+/-3dB) • 8 ohm • Continuous 100W / Music 200W / Peak 400W • 1" (25.4mm) Titanium Dome HF • Low distortion, high power woofers • High strength Trapezoidal cabinet • Pro-tech (Bulb) driver protection • M8 High Strength Hanging Points • Barrier strip • Supplied with an Adjustable Heavy Duty Steel Wall Bracket.		
<b>Programme205TWhite</b>	703340102600	375.00			
			2 x 5" two way 100W Installation speaker • as above in White		
<b>Programme206TBlack</b>	703340102488	520.00			
			2-Way, 6.5"x2 high power woofer • 65-20kHz frequency response (+/-3dB) • 8 ohm • Continuous 150W / Music 300W / Peak 600W • 1" (25.4mm) Titanium Compression Driver • Low distortion, high power woofers • High strength Trapezoidal cabinet • Pro-tech(Bulb) driver protection • M8 High Strength Hanging Points • Barrier strip • Supplied with an Adjustable Heavy Duty Steel Wall Bracket.		
<b>Programme206TWhite</b>	703340102600	520.00			
			2 x 6.5" two way 150W Installation speaker • as above in White		
<b>Programme406TBlack</b>	703340102969	895.00			
			2-Way, 6.5x4"high power woofer • 60-20kHz frequency response (+/-3dB) • 1" (25.4mm) Titanium Compression Driver • 8 ohm • Continuous 250W / Music 500W / Peak 1000W • Low distortion, high power woofers • High strength Trapezoidal cabinet • Pro-tech (Bulb) driver protection • M8 High Strength Hanging Points • Barrier strip • Supplied with an Adjustable Heavy Duty Steel Wall Bracket.		
<b>Programme406TWhite</b>	703340103089	895.00			
			4 x 6.5" two way 250W Installation speaker • as above in White		

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prix n'inclus pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com

rev\_1



**WARRANTY**  
Passive Speakers: 5 Years  
Electronics & Powered Speakers: 3 Years

**Erikson**  
**AUDIO**

Effective March 1, 2017 / En vigueur le 1 mars, 2017  
Replaces October 1, 2016 / Remplace le 24 février, 2016

Suggested Retail Price List

UPC	Sugg. Retail	UPC	Sugg. Retail
-----	--------------	-----	--------------

## SI-X Series - BAR, SCHOOL, WORSHIP

**The SI-X series is a painted wooden enclosure install series of full range speakers. Designed for installation and contractor market. Bracket mounting and aesthetic finish suitable for commercial audio applications.**

Angled low profile enclosures designed for unobtrusive **fixed install** where sonic accuracy and high SPL are essential. Consistent voicing across the range ensures seamless coverage when using a variety of models in distributed sound applications. The SI-X™ Series features a 1" compression driver on a 70 x 70 conical waveguide provides open and detailed high frequency extension with an even and predictable dispersion. Low profile subwoofer design to facilitate discreet operation in installations.

Because of the multi-faceted cabinet design, the SI-X™ speakers can be positioned on the floor as a stage monitor or mounted on a wall, ceiling or any venues as diverse as live performance halls, airports, and houses of worship, schools, retail shops, restaurants and public houses. Rugged cabinets feature 20 x M8 threaded inserts for safe installation. • Optional Brackets: WPB-1.

### SI-10XBlack

703340157808

520.00



10" 2-way • 60-20kHz frequency response(+/-3dB) • 8 ohm system impedance • Continuous 200W / Music 400W / Peak 800W • (HxWxD) 512x310x294mm • 13.6 kg

### SI-10XWhite

703340017522

520.00

as above in white

### SI-12XBlack

703340157921

575.00



12" 2-way • 60-20kHz frequency response(+/-3dB) • 8 ohm system impedance • Continuous 250W / Music 500W / Peak 1000W • (HxWxD) 562x333x344mm • 16.7 kg

### SI-12XWhite

703340017645

575.00

as above in White

### SI-15XBlack

703340158041

720.00



15" 2-way • 50-20kHz frequency response(+/-3dB) • 8 ohm system impedance • Continuous 400W / Music 800W / Peak 1600W • (HxWxD) 640x396x422mm • 24.6 kg

### SI-15XWhite

703340017768

720.00

as above in White

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prix n'inclus pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com

Page 10.

**JAM**  
copyright © Jam Industries Ltd.

rev\_1



**WARRANTY**  
Passive Speakers: 5 Years  
Electronics & Powered Speakers: 3 Years

**Erikson**  
**AUDIO**

Effective March 1, 2017 / En vigueur le 1 mars, 2017  
Replaces October 1, 2016 / Remplace le 24 février, 2016

Suggested Retail Price List

	UPC	Sugg. Retail	UPC	Sugg. Retail
--	-----	--------------	-----	--------------

## Titan Series

### Titan X Series - Passive

A REFRESH FOR OUR WORLD-FAMOUS 12" AND 15" PASSIVE TITAN MODELS. For many years the name 'Titan' has become the benchmark for portable and versatile loudspeakers. The new TITAN-X now features all-new HF and LF drivers. The HF has been completely reevaluated for both coverage and sound quality ensuring a much smoother sound, especially at high output. The all-new LF driver has improved moisture rejection characteristics which allows TITAN-X to be installed into hostile environments. We have also tweaked the laminar rib cabinet structure to improve structural strength for durability and acoustic performance. TITAN-X raises the bar for portable PA and is built to last.

**Titan-X12-BLK** 703341142445 430.00

Moulded Passive speaker 2-way 12 inch



**Titan-X12-WHT** 703341142568 430.00

Moulded Passive speaker 2-way 12 inch

**Titan-X15-BLK** 703341142681 620.00

Moulded Passive speaker 2-way 15 inch



**Titan-X15-WHT** 703341142803 620.00

Moulded Passive speaker 2-way 15 inch

### Titan Series - Passive

Compact and lightweight, Titan 8, Titan 12 and Titan 15 provide high output, punchy low end and extended high frequency response that is equally at home with music and speech. Compact, lightweight and affordable, the Titan Passive Series still packs professional drivers that deliver unmatched performance.

**Titan8-Grey**

703339901962

230.00



Two way passive speaker system • Frequency response +/- 3db: 70Hz-20kHz • Sensitivity (db 1w@1m): 96dB SPL • System impedance: 8 ohms • Maximum SPL Peak dB: 124dB SPL Peak • POWER HANDLING (Watts): Continuous RMS: 150W; Program: 300W; Peak: 600W • IN / OUT PANEL (speaker Level): Input connector: NLA Speakon™ type x2 " 1/4" phone jack x 2 (All wired in parallel) • **Finish: Titanium Grey** • **Construction material: Injection Molded Polypropylene** • Handle quantity: 1 built-in carry handle • Suspension points: 8 M6 threaded inserts including 4 M6 threaded inserts on bottom in OmniMount 30.0-type footprint • Stand adapter - BOTTOM: Pole-mount receptacle with lock screw, Optional wall-mount bracket • Height ( mm / ins ): 396mm / 15.59 " • Width Front / Rear / mm / ins: 266mm / 10.47 " • Depth ( mm / ins ): 221mm / 8.7 " • Net weight ( kg / lbs ): 5.5kg / 12.1 lbs • Gross weight ( kg / lbs ): 7.5kg / 16.5 lbs • Optional Brackets: WPB-2, 3, T8.

**Titan8-Black** 703340098408 230.00

as above in black

**Titan8-White** 703340014767 230.00

as above in white

**Titan12-Grey** 703339650082 405.00



12" 2-way passive • Frequency response +/- 3db: 55-20kHz • Sensitivity (db 1w@1m): 98dB • System impedance: 8 ohms • Maximum SPL Peak dB: 120dB • POWER HANDLING (Watts): Continuous RMS: 250; Program: 500; Peak: 1000 • Input connector: 2 x 1/4" jacks and 2 x Speakon™ • **Enclosure type: Molded Polypropylene** • **Finish: Titanium Grey** • Handle quantity: 2 carry handles (one on each side) • Suspension points: (10) M8 points for safe flown applications, (4) M8 inserts on bottom in OmniMount® 60.0-type footprint • Stand adapter - BOTTOM: Speaker pole-mount receptacle with lock screw, Optional wall-mount bracket • Stand adapter - TOP: Optional dual-unit array speaker stand hardware • Height ( mm / ins ): 556mm/21.88" • Width Front / Rear / mm / ins: 384mm/15.1" / 180mm/7.1" • Depth ( mm / ins ): 312mm/12.3" • Net weight ( kg / lbs ): 12kg/26.4lbs • Gross weight ( kg / lbs ): 14kg/30.8lbs • Optional Brackets: WPB-1, 2. **Limited supplies remaining.**

**Titan12-Black** 703340013920 405.00

as above in black **Limited supplies remaining.**

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Le produit avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prix n'inclus pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com

Page 11.

**JAM**  
copyright © Jam Industries Ltd.

Suggested Retail Price List

UPC	Sugg. Retail	UPC	Sugg. Retail
-----	--------------	-----	--------------

## Titan AX Series - Active

For many years the name 'Titan' has become the benchmark for portable and versatile loudspeakers. It's a name that is trusted by artists and venues around the world, day in, day out. However, technology advances... and so do we! Our all-new TITAN AX12 and AX15 active loudspeakers therefore now feature our cutting edge 6-position DSP engine and all-new HF and LF drivers. No other competitive model features such powerful and effective DSP. • What makes them great? • NEW - Category leading DSP functions • NEW - All new HF and LF drivers • NEW - Tweaked laminar rib structure • Integral mixer functions • TITAN AX is compatible with all current TITAN series mounting hardware and tourbags. • TITAN-AX12 600 Watts programme • TITAN-AX15 840 Watts programme

**Titan-AX12-Black** 703341189600 **665.00**  
Moulded ACTIVE speaker 2-way 12 inch



**Titan-AX12-White** 703341194284 **665.00**  
Moulded ACTIVE speaker 2-way 12 inch

**Titan-AX15-Black** 703341189600 **865.00**  
Moulded Active speaker 2-way 15 inch



**Titan-AX15-White** 703341194406 **865.00**  
Moulded Active speaker 2-way 15 inch

## Titan Series - Active

Titan Active Series models are 2-way bi-amplified, Class D technology is now used for the LF and HF, creating a more efficient and powerful system that is not only lighter than the previous generation but also offer low distortion and highly efficient performance. Additional features include LF and HF signal limiting and Hi/Low EQ Controls. The series also comes in wall mount bracket options, adding to its usefulness in large closed areas like concerts and theater. Being self powered they are easy to use and install, yet do not compromise on any professional features. They are protected for thermal, DC and short circuit faults making them one of safest speakers in the market.

**Titan8ActivemkII-Grey** 703340497683 **505.00**  
Powered full range speaker as above • 2-way bi-amp • Dual class D • Switch mode power supply • Horn LED defeat switch • 150W LF / 30W HF power output • Switchable mic/line input with XLR/TRS combo connector • 2 band EQ • Balanced line level XLR output. • Optional Brackets: WPB-2, 3, T8. Titanium Grey.



**Titan8ActivemkII-Black** 703340482689 **505.00**  
as above in black

**Titan8ActivemkII-White** 703340498529 **505.00**  
as above in white

**Titan12D** 703340652600 **605.00**  
Powered full range speaker as above with 250W + 50W Bi amp 8ohm • **Black only** -  
Now with:  
• Class D amplifier technology  
• Qubit™ 24-bit 192kHz DSP  
• Switched foldback monitor filter  
• Horn LED defeat switch  
• Remote gain control  
• Dual Class D power modules  
• Optional Brackets: WPB-1, 2.



**Titan15D** 703340658961 **749.00**  
Powered full range speaker as above with 350W + 70W Bi amp 8ohm • **Black only** -  
Now with:  
• Class D amplifier technology  
• Qubit™ 24-bit 192kHz DSP  
• Switched foldback monitor filter  
• Horn LED defeat switch  
• Remote gain control  
• Dual Class D power modules  
• Optional Brackets: WPB-1, 2.







**WARRANTY**  
Passive Speakers: 5 Years  
Electronics & Powered Speakers: 3 Years



Effective March 1, 2017 / En vigueur le 1 mars, 2017  
Replaces October 1, 2016 / Remplace le 24 février, 2016

### Suggested Retail Price List

	UPC	Sugg. Retail		UPC	Sugg. Retail	
<b>TitanSub-A12-Grey</b>	703340055326	910.00		<b>WPB-1-Black</b>	703339924046	105.00
			12" active bass-reflex subwoofer • Custom Wharfedale Pro 12" transducer • Preset integral peak limiter prevents signal distortion and amplifier clipping • Integral polarity reverse switch • Adjustable crossover frequency (80Hz – 200Hz in 6 steps) • Stereo balanced / unbalanced inputs on combi XLR / Jack • Stereo balanced HPF outputs on XLR • Integral carry handles and pole mount adapter • Finish: Titanium Grey			The WPB-1 is suitable for both Wharfedale Pro and Third-Party loudspeakers that feature an Omnimount™ 60.0 footprint, including SI-X and Titan 12/15 passive/active. Black.
<b>TitanSub-A12Black</b>	703340299089	910.00		<b>WPB-1-White</b>	703339924169	105.00
	As above in Black				as above in White.	
<b>TitanSub-A15MKII-Grey</b>	703340875689	1010.00		<b>WPB-2-Black</b>	703340483402	105.00
			Powerful 15" band-pass active subwoofer • Built-in 400 watt (continuous) 600 watt (peak) amplifier • Accepts stereo or mono line level inputs via dual, balanced, XLR- " "combo" connectors as well as a unique single channel 4 ohms speaker level input via a " "phone jack which allows for use with a standard sound reinforcement amplifier (when the internal amplifier is not used) • Custom designed, down-firing, aluminium cast frame 15" woofer, with 3" voice coil • Integral signal processing includes a dynamic AGC (Automatic Gain Control) circuit, a stereo crossover and signal limiting for the prevention of a distorted signal to the internal amplifier • PHASE switch • A pair of balanced XLR male output connections, with switchable "High-Pass" mode for stereo line level outputs • Pole mount socket • Integral Carry Handle • Rubber Feet • Two ports on front are reflex tuned to provide enhanced low frequency response • Height: 630.0mm / 24.8" • Width: 478.0mm / 18.8" • Depth: 640.0mm / 25.2" • Weight (Net) kg / lbs: 45.48 / 100.0 • Weight (Gross) kg / lbs: 50.48 / 110.5 • Finish: Titanium Grey			The WPB-2 is suitable for all Wharfedale Pro loudspeakers that feature a pole mount socket and weigh under 22Kg. Black.
<b>TitanSub-A15MKII-Black</b>	703340874842	1010.00		<b>WPB-2-White</b>	703340496846	105.00
	As above in Black				As above in White.	
<b>Titan8NylonTouringBag</b>	703340008407	59.00		<b>WPB-T8-Black</b>	703340297405	55.00
	BAG for molded Titan 8 inch				The WPB-T8 is suitable for Titan 8 and Titan 8A/8A MKII, providing a secure and versatile mounting. Black.	
<b>Titan12NylonTouringBag</b>	703339680805	69.00		<b>WPB-T8-White</b>	703340297528	55.00
	BAG for molded Titan 12 inch				As above in White.	
<b>Titan15NylonTouringBag</b>	703339774405	129.00				
	BAG for molded Titan 15 inch					

## Brackets & Poles

<b>SP-1</b>	703339919004	99.00
	Speaker pole mount for standard cup.	
<b>SP-2</b>	703340019809	105.00
	Speaker Pole with thread attachment	

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prices n'incluent pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com



Suggested Retail Price List

	UPC	Sugg. Retail		UPC	Sugg. Retail
<b>Connect Series Mixers</b>			<b>SL Series Mixers</b>		
<p>The Connect Series from Wharfedale Pro are high quality micro-mixers suitable for a wide range of applications.</p> <p>Professional big mixer features such as Phantom power and balanced XLR mic inputs deliver full functionality and great sound in an ultra compact and cost effective package that is ideal for live sound, home studio recording and fixed installations. The Mic pre-amps use the same high quality components and construction methods employed in SL Series Mixers.</p> <p>All Connect Series models feature an intuitive, ergonomically designed user interface, excellent for beginners and professionals alike. Comprehensive connectivity ensures Connect mixers will fit many applications.</p>					
<b>Connect502USB</b>	703340694846	155.00	<b>SL424USB</b>	703340778485	475.00
Switchable Global +48V Phantom Power • Clip LED's on Mic/Line Channels • 1 x Balanced XLR Mic Input • Pan/Balance Controls On All Channels • 2 x Stereo Channels with Balanced/Unbalanced 1/4" TRS Jacks • Separate Main Mix and Phones Outputs with Level Controls • Stereo 4 Segment LED Meters • Stereo 1/8" and 1/4" Headphone Outputs • 2x2 USB computer interface.				Compact studio/live mixing console • Suitable for a wide range of mid format mixing duties in both live sound and home studio applications • Full Duplex 2 In/2 Out 16-Bit 48kHz USB Interface • 4 Studio Grade Phantom Powered Mic Pre-Amps • Ultra Musical 3-Band EQ with High Pass Filters • 1 Auxiliary Send • Dedicated Stereo Return with Level Control • Pan and Balance Controls • Control Room and Headphone Outputs • Master Outputs with XLR and TRS Connectors.	
<b>Connect802USB</b>	703340695560	199.00	<b>SL824USB</b>	703340517244	865.00
Switchable Global +48V Phantom Power • Clip LED's on Mic/Line Channels • 2 x Balanced XLR Mic Input • Pan/Balance Controls On All Channels • 2 x Stereo Channels with Balanced/Unbalanced 1/4" TRS Jacks • Separate Main Mix and Phones Outputs with Level Controls • Stereo 4 Segment LED Meters • Stereo 1/8" and 1/4" Headphone Outputs • 2x2 USB computer interface.				The SL 824 mixer is a studio/live mixing console with built-in full duplex USB interfacing. Engineered to cater to a wide range of mid format mixing duties, the SL 824 includes many features suited to both live sound and home studio applications • Full Duplex 2 In/2 Out 16-Bit 48kHz USB Interface Dedicated USB Recording Bus • Switchable Line/USB Return Channel • 8 Studio Grade Phantom Powered Microphone Pre-Amps • Ultra Musical 3-Band EQ with High Pass Filters • Built-In Digital FX with Dedicated Send • 2 Auxiliary Sends • Dedicated Stereo Return with Level Control • Pan and Balance Controls • PFL for All Channels • Control Room and Headphone Outputs • Master Outputs with XLR and TRS Connectors	
<b>Connect1002FXUSB</b>	703340946129	299.00	<b>SL1224USB</b>	703340608683	1080.00
	Compact professional 10-channel mixer • 2 Mono Mic/Line Channels and 4 Stereo Channels • Input Gain Controls On All Mono Channels • Ultra musical 3 band EQ with high pass filters On All Mono Channels • Built-in digital FX with dedicated send, 56 effects • Pan or balance controls, Stereo 4 Segment LED Meters • Control room and headphone outputs, 2TK to Mains/ Headphones Level Control • Master outputs with TRS connectors, Clip LED on Mic/Line Channels • Bi-directional USB connection 2x2 interface			A studio/live mixing console with built-in full duplex USB interfacing. Engineered to cater to a wide range of mid format mixing duties • Includes many features suited to both live sound and home studio applications • Full Duplex 2 In/2 Out 16-Bit 48kHz USB Interface Dedicated USB Recording Bus • Switchable Line/USB Return Channel • 12 Studio Grade Phantom Powered Microphone Pre-Amps • Ultra Musical 3-Band EQ with High Pass Filters • Built-In Digital FX with Dedicated Send • 2 Auxiliary Sends • Dedicated Stereo Return with Level Control • Pan and Balance Controls • PFL for All Channels • Control Room and Headphone Outputs • Master Outputs with XLR and TRS Connectors.	
<b>Connect1202FXUSB</b>	703340946969	330.00			
	Compact professional 12-channel mixer • 4 Mono Mic/Line Channels and 4 Stereo Channels • Input Gain Controls On All Mono Channels • Ultra musical 3 band EQ with high pass filters On All Mono Channels • Built-in digital FX with dedicated send, 56 effects • Pan or balance controls, Stereo 4 Segment LED Meters • Control room and headphone outputs, 2TK to Mains/ Headphones Level Control • Master outputs with TRS connectors, Clip LED on Mic/Line Channels • Bi-directional USB connection 2x2 interface				

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prix n'inclus pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com

Suggested Retail Price List

UPC	Sugg. Retail	UPC	Sugg. Retail
-----	--------------	-----	--------------

## Integrated Amplifier

### MA5220

703340952007

1080.00



Integrated amplifier • Ideal for public installation • Low impedance (40ohms/160ohms) operation • Constant voltage (100v/70.7v line) operation • 3 Line inputs, 2 Microphone Inputs • Screw Connector Outputs • Additional line outputs • +24v Phantom Power • HPF / LPF on each channel • 2 Band Master EQ • 8-Segment LED For Level and Protect Display • Built-in Limiter • Adjustable ducking feature • Variable speed fan cooling • Power: 2 x 200W RMS • Operation: 4 Ohms low-impedance, 110v / 70.7v • Inputs: 3 x RCA Phono, 2 x 6.3mm Jack • Outputs: 2 x Screw Terminal, 1 x RCA Phono, 2 x 6.3mm jack • EQ: Bass +/- 10dB at 100Hz • Treble +/- 10dB at 12kHz • Filter: HPF 60Hz +/-3dB • LPF 16Hz +/-3dB • Ducking Control: Threshold / Reduction • Phantom Power: 24v • Remote Control: Range @ -45dB • Frequency Response: 20Hz - 20kHz +/-3dB • Signal To Noise Ratio: >85dB • Crosstalk: >73dB • Input Impedance: 10k Ohms (line unbalanced) • 600 Ohms (microphone) • Display: 8 Segment LED • Protection: Limiter, Fan Cooling • Dimensions: 430mm x 360mm x 86mm • Weight: 11.2kg / 24.69lbs

## Speaker Switches

### VersadriveSC-26

703340981281

1010.00



Speaker management system • 1U rack design, • Intuitive and concise front panel with LCD screen • takes control of crossover, EQ and limiter • With USB and RS485 connectivity Versadrive can be networked and controlled using supplied software directly from PC. • 32-bit DSP processor and 24-bit A/D and D/A converter • 6 balanced XLR outputs working independently for use with any combination of loudspeakers • Crossover features linkwitz-riley, bessel and butterworth modes all of which can be used in typical stereo crossover formations, or as individual high-pass and low-pass filters on each channel • Output EQ : low-shelf, high-shelf and parametric with central control • Password locking • Out of the box the Versadrive SC-26 comes equipped with optimised settings for popular Wharfedale Pro loudspeaker configurations including WLA, Delta and EVP-X MKII - 30 programme memory with ability to copy channel parameters • Link up to 250 units, with remote control from up-to 1500 meters. With the Versadrive SC-26 the possibilities are endless.

rev\_1



**WARRANTY**  
Passive Speakers: 5 Years  
Electronics & Powered Speakers: 3 Years

**Erikson**  
**AUDIO**

Effective March 1, 2017 / En vigueur le 1 mars, 2017  
Replaces October 1, 2016 / Remplace le 24 février, 2016

Suggested Retail Price List

UPC	Sugg. Retail	UPC	Sugg. Retail
-----	--------------	-----	--------------

## Quad Industrial Products

### Quad Industrial Ordering Information

All models are **sold in pairs (prices indicated are per pair)** with the exception of the Concourse QSUB which may be ordered singly.

## C Series

Concourse C models deliver exceptional fidelity in a wide range of ceiling mounted speaker applications. With two full range models and an in-ceiling subwoofer the Concourse C line offers enough variety to satisfy nearly any requirement from paging to speech reinforcement and foreground music. • Complete, integrated ceiling mounted 2 speaker systems • Multiple termination options with conduit capability • Unique two-way designs utilizing genuine QUAD drivers • **Supplied with all mounting accessories for ceiling tile installation (C Clamp & Rail)** • Integral steel back boxes come fully assembled • Integral 70/100V line transformers with multiple power taps.

**ConcourseC4** 703340177127 **420.00**  
**Price is per pair. Must be ordered in pairs.**



2 way ceiling speaker 4" cone, switchable 70v / low impedance • Power Handling: Continuous 25W; Program 50W; Peak 100W • Integral 30/15/7.5/3.75 watt tap line transformer • Frequency Response: 55Hz 20kHz (10dB); 70Hz 20kHz (+/- 3dB) • Sensitivity (@2.83V): 84dB • Impedance: 4 & 16 ohm switchable • Max SPL: 104dB • Coverage (H x V): 110° x 90° • Directivity (Q): 5.34 • Transducers: LF Driver Size 4" Cone; HF Driver Size 1" Soft Dome Tweeter • Crossover Frequency: 2.2kHz • "C" ring included. Enclosure Material: Plastic (ABS) with metal back can • Connector Type: Screw Terminal • Dimensions (W x D): 252 x 219mm / 9.92" x 8.62" • Net Weight: 2.75kg / 6.05lbs.

**ConcourseC8** 703340193561 **640.00**  
**Price is per pair. Must be ordered in pairs.**



2 way ceiling speaker 8" cone, switchable 70v / low impedance • Power Handling: Continuous 75W; Program 150W; Peak 300W • Integral 60/30/15/7.5 watt tap line transformer • Frequency Response: 45Hz 20kHz (10dB); 55Hz 20kHz (+/- 3dB) • Sensitivity (@2.83V): 88dB • 70/100 volt plus low impedance operation 4 & 16 ohm switchable • Max SPL: 113dB • Coverage (H x V): 110° x 90° • Directivity (Q): 5.82 • Transducers: LF Driver Size 8" Cone; HF Driver Size 1" Soft Dome Tweeter • Crossover Frequency: 2.3kHz • Enclosure Material: Plastic (ABS) with metal back can • Connector Type: Screw Terminal • Dimensions (W x D): 333 x 238mm; 13.11" x 9.37" • Net Weight: 5.3kg / 11.66lbs.

### ConcourseCsub

703339410921

770.00

**Price is per pair. Must be ordered in pairs.**



10" long throw ceiling subwoofer, switchable 70v / low impedance • Power Handling: Continuous 100W; Program 200W; Peak 400W low impedance • Integral 100/30/15/7.5 watt tap line transformer • Frequency Response: 28Hz 500Hz (10dB); 43Hz 120kHz (+/- 3dB) • Sensitivity (@2.83V): 80dB • Low Impedance: 4 & 16 ohm Switchable • Max SPL: 106dB • Transducers: LF Driver Size 10" Long Throw • Crossover Frequency: 150Hz LPF • Enclosure Material: Plastic (ABS) metal back can • Connector Type: Screw Terminal • Dimensions (W x D): 371 x 349mm; 14.6" x 13.74" • Net Weight: 9.4kg / 20.68lbs.

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.  
PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.  
Prix n'inclut pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com


www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com

Page 16.

**JAM**  
copyright © Jam Industries Ltd.

Suggested Retail Price List

	UPC	Sugg. Retail		UPC	Sugg. Retail
<b>Q Series Compact Enclosures</b>					
For traditional surface mount applications choose from the Q4, Q5, Q6 or Q8. Each model delivers superior response and articulation by using genuine QUAD transducers with sophisticated crossover networks. All models are available in low impedance or 70/100V versions, while the Q6 and Q8 are also available as self-powered models for AV and monitoring applications. For diffuse sound applications choose between the unique bi-pole configurations of the D4 and D5. Add the Q-Sub in either passive or powered version to complete your system.					
					
<b>ConcourseQ4</b> (Black/White)	703340196081	265.00	<b>ConcourseQ6T</b> (Black/White)	703339572681	535.00
		<b>Price is per pair. Must be ordered in pairs.</b>			<b>Price is per pair. Must be ordered in pairs.</b>
		2 Way, 4" Cone, 50w • Power Handling: Continuous 25W; Program 50W; Peak 100W • Frequency Response: 60Hz 20kHz (10dB); 100Hz 20kHz (+/- 3dB) • Sensitivity (@2.83V): 84dB • Impedance: 8 ohm • Max SPL: 105dB • Coverage (H x V): 110° x 130°; Directivity (Q): 6.62 • Transducers: LF Driver Size 4" Cone; HF Driver Size 1" Soft Dome • Crossover Frequency: 2.8kHz • Enclosure Material: Plastic (ABS) • Connector Type: Screw Terminal • Dimensions (HxWxD): 232 x 160 x 148mm; 9.1" x 6.3" x 5.8" • Net Weight: 2.1kg/ 4.6lbs.			2 way, 6.5" cone, 70/100 volt. • Power handling: 70V- 12.5w, 25w, 50w. 100V- 12.5w, 50w. • Frequency Response: 50Hz 20kHz (10dB); 70Hz 17kHz (+/- 3dB) • Sensitivity (@2.83V): 86dB • Impedance: N/A • Max SPL: 109dB • Coverage (H x V): 150° x 170° • Directivity (Q): 6.3 • Transducers: LF Driver Size 6.5" Cone; HF Driver Size 1" Soft Dome • Crossover Frequency: 2.2kHz • Enclosure Material: Plastic (ABS) • Connector Type: Screw Terminal • Dimensions (HxWxD): 370 x 245 x 216mm; 14.6" x 9.6" x 8.5" • Net Weight: 3.7kg/ 8.14lbs. • Black or White.
<b>ConcourseQ4T</b> (Black/White)	703340197040	320.00	<b>ConcourseQ8</b> (Black/White)	703339607727	465.00
		<b>Price is per pair. Must be ordered in pairs.</b>			<b>Price is per pair. Must be ordered in pairs.</b>
		2 way, 4" cone, 70/100volt • Power Handling: 70V-3.75w, 7.5w, 15w, 100V-7.5w, 15w • Frequency Response: 60Hz 20kHz (10dB); 100Hz 20kHz (+/- 3dB) • Sensitivity (@2.83V): 84dB • Impedance: N/A • Max SPL: 105dB • Coverage (H x V): 110° x 130°; Directivity (Q): 6.62 • Transducers: LF Driver Size 4" Cone; HF Driver Size 1" Soft Dome • Crossover Frequency: 2.8kHz • Enclosure Material: Plastic (ABS) • Connector Type: Screw Terminal • Dimensions (HxWxD): 232 x 160 x 148mm; 9.1" x 6.3" x 5.8" • Net Weight: 2.1kg/ 4.6lbs.			2 way, 8" cone, 100w • Power Handling: Continuous 50W; Program 100W; Peak 200W • Frequency Response: 50Hz 20kHz (10dB); 70Hz 20kHz (+/- 3dB) • Sensitivity (@2.83V): 87dB • Impedance: 8 ohm • Max SPL: 110dB • Coverage (H x V): 130° x 180° • Directivity (Q): 6.59 • Transducers: LF Driver Size 8" Cone; HF Driver Size 1" Soft Dome • Crossover Frequency: 2.0kHz • Enclosure Material: Plastic (ABS) • Connector Type: Screw Terminal • Dimensions (HxWxD): 405 x 270 x 234mm; 15.9" x 10.63" x 9.2" • Net Weight: 4.3kg/ 9.46lbs. • Black or White.
<b>ConcourseQ6</b> (Black/White)	703339641929	410.00	<b>ConcourseQ8T</b> (Black/White)	703339608441	610.00
		<b>Price is per pair. Must be ordered in pairs.</b>			<b>Price is per pair. Must be ordered in pairs.</b>
		2 way, 6.5" cone, 100w • Power Handling: Continuous 50W; Program 100W; Peak 200W • Frequency Response: 50Hz 20kHz (10dB); 70Hz 17kHz (+/- 3dB) • Sensitivity (@2.83V): 86dB • Impedance: 8 ohm • Max SPL: 109dB • Coverage (H x V): 150° x 170° • Directivity (Q): 6.3 • Transducers: LF Driver Size 6.5" Cone; HF Driver Size 1" Soft Dome • Crossover Frequency: 2.2kHz • Enclosure Material: Plastic (ABS) • Connector Type: Screw Terminal • Dimensions (HxWxD): 370 x 245 x 216mm; 14.6" x 9.6" x 8.5" • Net Weight: 3.7kg/ 8.14lbs. • Black or White.			2 way, 8" cone, 70/100 volt • Power Handling: 70V- 12.5w, 25w, 50w. 100V- 12.5w, 50w. • Frequency Response: 50Hz 20kHz (10dB); 70Hz 20kHz (+/- 3dB) • Sensitivity (@2.83V): 87dB • Impedance: N/A • Max SPL: 110dB • Coverage (H x V): 130° x 180° • Directivity (Q): 6.59 • Transducers: LF Driver Size 8" Cone; HF Driver Size 1" Soft Dome • Crossover Frequency: 2.0kHz • Enclosure Material: Plastic (ABS) • Connector Type: Screw Terminal • Dimensions (HxWxD): 405 x 270 x 234mm; 15.9" x 10.63" x 9.2" • Net Weight: 4.3kg/ 9.46lbs. • Black or White.
			<b>ConcourseQSUB(Black)</b>	703339740202	610.00
					<b>Price Is Each.</b>
					Sub-woofer, 10" Dual Voice Coil Cone, 250w • Power Handling: 2 x 125W; 2 x 250W; 2 x 500W • Frequency Response: 35Hz 420Hz (10dB); 42Hz 350Hz (+/- 3dB) • Sensitivity (@2.83V): 82dB • Impedance: Left 8 ohm/Right 8 ohm • Transducers: 1x LF Driver Size 10" Long Throw Dual Voice Coil • Crossover Frequency: 150Hz • Built-in passive network for satellite speakers. Enclosure Material: Wood (MDF) • Connector Type: 2 x Terminal Strip • Dimensions (HxWxD): 585 x 372 x 316mm; 23" x 14.6" x 12.4" • Net Weight: 14.2kg/ 31.2lbs.

rev\_1



**WARRANTY**  
Passive Speakers: 5 Years  
Electronics & Powered Speakers: 3 Years

**Erikson**  
**AUDIO**

Effective March 1, 2017 / En vigueur le 1 mars, 2017  
Replaces October 1, 2016 / Remplace le 24 février, 2016

Suggested Retail Price List

UPC	Sugg. Retail	UPC	Sugg. Retail
-----	--------------	-----	--------------

## "R" Series Architectural In-wall Speakers

Two-way, high performance, in-wall / on-ceiling mounted speaker systems for distributed music, paging and speech applications. Packaged in pairs. Premium drive units with a discrete ABS front baffle and attractive metal grille. Unique mounting system for easy installation. Mounting bars and screws, plastic paint covers and cardboard cutout templates included.

- Complete, integrated ceiling / wall mounted speaker systems
- Multiple termination options with conduit capability
- Unique two-way designs utilizing genuine QUAD drivers
- All systems are CE rated.

### ConcourseR6

703340193080

270.00

**Price is per pair. Must be ordered in pairs.**



2 way in-wall speaker 6" cone , 100w • Power Handling: Continuous 50W; Program 100W; Peak 200W • Frequency Response: 40Hz 20kHz ( 10dB); 70Hz 16kHz (+/- 3dB) • Sensitivity (@2.83V): 89dB • **Impedance: 4 ohm** • Max SPL: 112dB • Coverage (H x V): 140° x 110° • Directivity (Q): 6.14 • Transducers: LF Driver Size 6.5" Cone; HF Driver Size 1" Soft Dome Tweeter • Crossover Frequency: 2.3kHz • Enclosure Material: Plastic (ABS) • Connector Type: Screw Terminal • Dimensions (HxWxD): 332 x 232 x 92mm; 13.07" x 9.14" x 3.62" • Net Weight: 1.8kg/ 3.7lbs.

### ConcourseR8

703339534047

505.00

**Price is per pair. Must be ordered in pairs.**



3 way in-wall speaker 8" cone , 200w • Power Handling: Continuous 100W; Program 200W; Peak 400W • Frequency Response: 35Hz 20kHz ( 10dB); 45Hz 20kHz (+/- 3dB) • Sensitivity (@2.83V): 90dB • **Impedance: 4 ohm** • Max SPL: 115dB • Coverage (H x V): 130° x 100° • Directivity (Q): 6.82 • Transducers: Driver Size LF: 8" Cone/MF: 2" Soft Dome; HF: 1" Soft Dome Tweeter • Crossover Frequency: 1.2kHz & 5.2kHz • Enclosure Material: Plastic (ABS) • Connector Type: Spring-loaded Terminal • Dimensions (HxWxD): 444 x 284 x 110mm; 17.48" x 11.18" x 4.33" • Net Weight: 4.8kg/ 10.56lbs.

Any product with MAP is subject to the terms & conditions of the Erikson Audio MAP policy.

PRICES DO NOT INCLUDE TAXES AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. POSSESSION OF THIS PRICE LIST DOES NOT REPRESENT DEALER STATUS.

Les produits avec le prix "MAP" sont soumis aux termes et conditions de la politique PMA d'Erikson Audio.

Prix n'inclus pas les taxes et sont sujets à changement sans préavis. La possession de cette liste de prix ne confère pas automatiquement le statut de marchand.

Orders/Commandes: 1-800-667-3745 • Fax Orders/Commandes: 888-918-2244 or/ou 514-457-4986

Service Toll Free/Sans frais: 1-877-JAM-LINE • Service Fax: 1-800-563-2591

Tech. Support (not incl. repairs): 1-888-816-2333 • Tech. Support Email: bill.kinal@eriksonaudio.com

www.eriksonaudio.com • Electronic Price List Requests (please specify your requirements): benjamin.russell@jamindustries.com

Head Office - Siège Sociale Montréal 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-0055 • email: info@eriksonaudio.com

Page 18.

**JAM**  
copyright © Jam Industries Ltd.