

Video Panels

PVPX3X8 8 panels in road case

Optical:

Light Source: 16,384 LEDs (tri-color RGB) SMD 2121, 50,000 hours life expectancy

Color Wavelength: red (625 nm), green (525 nm), blue (470 nm)

Viewing Angle: 130°

Illuminance: 1,560 NITS

Pixels: 128 x 128

Pixel Pitch: 3.9 mm

Pixel Density: 65,536/m²

Display Refresh Rate: 2,400 Hz

Construction:

Dimensions: 19.7 x 3.5 x 20.35 in (500 x 89 x 517 mm)

Weight: 18.7 lb (8.5 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Maximum vertical hang: 20 panels

Transparency: 0%

Electrical:

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)



19,111.00

PVPX6IPX8 8 panels in road case

Optical:

Light Source: 5,184 LEDs (tri-color RGB) SMD 2623, 50,000 hours life expectancy

Color Wavelength: red (625 nm), green (525 nm), blue (470 nm)

Viewing Angle: 130°

Illuminance: 4,500 NITS

Pixels: 72 x 72

Pixel Pitch: 6.9 mm

Pixel Density: 20,736/m²

Display Refresh Rate: 3,120 Hz

Construction:

Dimensions: 19.7 x 3.27 x 20.35 in (500 x 83 x 517 mm)

Weight: 19.8 lb (9 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Transparency: 8%

Electrical:

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 17 units @ 120 V, 28 units @ 208 V, 70 units @ 230 V



20,848.00

C6 4 panels in wooden crate

Optical:

Light Source: 12,800 LEDs (tri-color RGB) SMD 3528, 50,000 hours life expectancy
Color Wavelength: red (620 to 625 nm), green (524 to 529 nm), blue (467 to 470 nm)

Viewing Angle: 140°

Illuminance: 1,500 NITS

Pixels: 80 x 160

Pixel Pitch: 6.25 mm

Pixel Density: 25,600/m²

Display Refresh Rate: 1,080 Hz

Construction:

Dimensions: 39.4 x 19.7 x 2.5 in (1,000 x 500 x 63 mm)

Weight: 23 lb (10.4 kg)


Exterior Color: Black

Housing Material: Aluminum alloy

Transparency: 0%

Electrical:

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)



11,744.00

F4X4 4 panels in a flight case

Optical:

Light Source: 21,632 LEDs (tri-color RGB) SMD 2828, 50,000 hours life expectancy
Color Wavelength: red (619 to 624 nm), green (522 to 525 nm), blue (468 to 471 nm)

Viewing Angle: 140°

Illuminance: 1,500 NITS

Pixels: 104 x 208

Pixel Pitch: 4.8 mm

Pixel Density: 43,264/m²

Display Refresh Rate: 3,840 Hz

Construction:

Dimensions: 19.69 x 1.89 x 39.37 in (500 x 48 x 1000 mm)

Weight: 28.4 lb (12.88 kg)

Exterior Color: Black

Housing Material: Magnesium die-cast panels

Maximum vertical hang: 16

Maximum horizontal hang: 22 panels

Transparency: 0%

Electrical:



14,246.00

F4X4IP 4 panels included

Optical:

Light Source: 21,632 LEDs (tri-color RGB) SMD 1921, 50,000 hours life expectancy
Color Wavelength: red (619 to 624 nm), green (522 to 525 nm), blue (468 to 471 nm)

Viewing Angle: 140°

Illuminance: 5,500 NITS

Pixels: 104 x 208

Pixel Pitch: 4.8 mm

Pixel Density: 43,264/m²

Display Refresh Rate: 3,840 Hz

Construction:

Dimensions: 19.69 x 1.89 x 39.37 in (500 x 48 x 1000 mm)

Weight: 28.6 lb (12.88 kg)

Exterior Color: Black

Housing Material: Magnesium die-cast *Maximum vertical hang:* 16 panels

Maximum horizontal hang: 22 panels

Transparency: 0%



18,068.00

F3X4 4 panels included

Optical:

Light Source: 65,536 LEDs (tri-color RGB) SMD 2121, 50,000 hours life expectancy
Color Wavelength: red (619 to 624 nm), green (522 to 525 nm), blue (468 to 471 nm)

Viewing Angle: 140°

Illuminance: 1,200 NITS

Pixels: 128 x 256

Pixel Pitch: 3.9 mm

Pixel Density: 65,536/m²

Display Refresh Rate: 3,840 Hz

Construction:

Dimensions: 19.69 x 1.89 x 39.37 in (500 x 48 x 1000 mm)

Weight: 28.6 lb (12.88 kg)

Exterior Color: Black

Housing Material: Magnesium die-cast *Maximum vertical hang:* 16 panels

Maximum horizontal hang: 22 panels

Transparency: 0%



15,636.00

Rigging Bars

RBX50CM X-series™ Rig Bar is used to hang video panels vertically

Works with CHAUVET® Professional X-Series video panels (PVP™ X3, PVP™ X6IP)

Load Capacity: 600 lb (272 kg)

Fitted: M20 Eyebolt (5/8" shackle recommended)

Weight: 11.4 lb (5.2 kg)

Dimensions: 23.15 x 5.12 x 6.46 in (588 x 130 x 164 mm)

Includes 1 x RB-XEBK



378.00

RBX200CM X-series™ Rig Bar is used to hang video panels vertically
Works with CHAUVET® Professional X-Series video panels (PVP™ X3, PVP™ X6(P))
Load Capacity: 920 lb (417 kg)
Fitted: M20 Eyebolt (5/8" shackle recommended)
Weight: 40 lb (18.1 kg)
Dimensions: 82.20 x 5.12 x 6.46 in (2,088 x 130 x 164 mm)
Includes 2 x RB-XEBK



941.00

RB-F100CM F-series™ Rig Bar is used to hang video panels vertically
Works with CHAUVET® Professional F-Series Video Panels (F4)
Load Capacity: 650 lb (295 kg)
Fitted: M20 Eyebolt (5/8" shackle recommended)
Weight: 17.6 lb (5.2 kg)
Dimensions: 40.75 x 2.56 x 2.76 in (1,035 x 65 x 70 mm)



441.00

RB-F50CMX2 F-series™ Rig Bars is used to hang video panels vertically or horizontally
Works with CHAUVET® Professional F-Series Video Panels (F4)
Load Capacity: 650 lb (295 kg)
Eyebolts replaceable with preferred mounting hardware (such as 2 inch truss clamps)
Weight: 9.0 lb (4 kg) each
Dimensions: 21.07 x 2.56 x 2.76 in (535 x 65 x 70 mm) each



478.00

PVP-RK Video wall hanging hardware that works with the C6 video panels
Includes half-coupler clamp for truss/pipe mounting
Load Capacity: 400 lb (200 kg)
Panels (vertical): 20 max. pieces
Fits: 2 inch (50 mm) truss
Weight: 3 lb (1.4 kg)
Dimensions: 8 x 1.5 x 8 in (203 x 38 x 203 mm)



172.00

RB-XEBK Eye Bolt Kit for RB-X rigging bars

73.00

CT-APP X-series™ Rig Bar is used to hang video panels vertically
Works with CHAUVET® Professional X-Series video panels (PVP™ X3, PVP™ X6/P)
Load Capacity: 600 lb (272 kg)
Fitted: M20 Eyebolt (5/8" shackle recommended)
Weight: 11.4 lb (5.2 kg)
Dimensions: 23.15 x 5.12 x 6.46 in (588 x 130 x 164 mm)
Includes 1 x RB-XEBK



328.00

Accessories

MT-01 Magnetic LED module replacement tool for the PVPX3



661.00

MT-03 Magnetic LED module replacement tool for the F4

698.00

Arkaos Media Master Express + KN Media Server Software

- Kling-Net support for easy plug-and-play configuration of EPIX™ and Nexus™ products
- Content DVD included (25 text layers, 26 Audio Visualizations, 169 source visuals)
- Support for SD & HD (includes AVI, MPEG, MPG, MOV, WMV, MP4, JPEG, GIF, BMP, PNG, SWF & more)
- Up to 4,096 user-configurable layers
- Easy to use interface



2,803.00

Arkaos Media Master Express + KN+ 1 x ENTTEC DMX USB Pro Media Server Software

- Kling-Net support for easy plug-and-play configuration of EPIX™ and Nexus™ products
- Content DVD included (25 text layers, 26 Audio Visualizations, 169 source visuals)
- Support for SD & HD (includes AVI, MPEG, MPG, MOV, WMV, MP4, JPEG, GIF, BMP, PNG, SWF & more)
- Up to 4,096 user-configurable layers
- Easy to use interface
- Includes 1 x ENTTEC DMX USB Pro Mk2



3,226.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclut pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

PVP XMH PVP X-Series Mounting Hardware

Designed to work for a variety of installation types
Works with CHAUVET® Professional X-Series video panels (PVP™ X3, PVP™ X6IP)
Dimensions (mounting plate): 3.15 x 2.48 x 0.67 in (80 x 63 x 17 mm)
Weight: 8.4 lb (3.81kg)
Includes
Long allen screw x 40
Short allen screw x 40
Washer x 40
Lock washer x 40

Mounting Plate x 10



150.00

VIP Drive 21L Video wall driver for use with Linsn

Video driver used to convert standard video signals (DVI) to Ethernet-based video wall protocol
Required for panel calibration and video conversion to CHAUVET LINSN-based video panels
CHAUVET LED Studio software connects directly to the VIP Drive 21L via USB for panel configuration
2 RJ-45 Ethernet outputs (655,360 LEDs capacity each, 1,310,720 total)



1,042.00

VIP Drive 43S All-in-one video wall mapper/scaler/switcher designed for use with Linsn video control protocol

Eliminates the need for individual mappers, scalers and video switchers
Supports DVI, HDMI AND HD-SDI
Includes 4 x Neutrik etherCON video outputs
Capable of up to full HD at 2.6 million LEDs)



4,343.00

VIP Drive 43N All-in-one video wall mapper/scaler/switcher designed for use with Novastar video control protocol

Eliminates the need for individual mappers, scalers and video switchers
Supports DVI, HDMI AND HD-SDI
Includes 4 x Neutrik etherCON video outputs
Capable of up to full HD at 2.6 million LEDs)



6,081.00

VIP Signal Distributor *Distributes and amplifies the output from the VIP Driver (must not exceed LED quantity capacity)*
Serves as a 2-channel, 4-way or 1-channel, 8-way device (requires 2 VIP Drivers)
You may link multiple units together for greater quantities
Required for signal cable runs over 100 m (serves as a signal amplifier)
Power Connection: Edison (Local) plug to IEC
Power Input: IEC
Cable Length (power): 5 ft (1.5 m)
Video Input: Neutrik etherCON(2)
Video Output: Neutrik etherCON(8)



1,077.00

VIP 5162 Signal Processor *Video processor ideal for LED screens and video projectors*
Capable of independent horizontal and vertical scaling of the video source
Control the brightness and X/Y positioning of the video
13 video input sources: CV(3), HD-SDI(1), USB(2), DVI(3), VGA, YPbPr(2), DisplayPort (2)
3 video outputs: DVI(2), VGA(1)
A dedicated playback monitor with seamless switching and video transitions (cut, instant, blackout, freeze) make this perfect for live video switching control
Play video content directly from the USB input using a flash drive, without a media server
Picture-in-picture, brightness, contrast, color calibration, and cropping are available
Control the unit via the PC software (USB, RS232, LAN) or front-surface controls
6 user presets are available
Output up to 2560 816/2048 1152 resolution (NTSC/PAL)
High quality, seamless switching
Includes VIP 5162 remote network control software



7,986.00

Cables

ETHERCONEXT18IN <i>Ethercon Extension - 18 inches</i>	46.00
ETHERCONEXT5FT <i>Ethercon Extension - 5 feet</i>	52.00
ETHERCONEXT10FT <i>Ethercon Extension - 10 feet</i>	78.00
ETHERCONEXT25FT <i>Ethercon Extension - 25 feet</i>	136.00
ETHERCONEXT50FT <i>Ethercon Extension - 50 feet</i>	192.00
POWERCONEXT18IN <i>PowerCon Extension - 18 Inches</i>	76.00
POWERCONEXT5FT <i>PowerCon Extension - 5 feet</i>	82.00
POWERCONEXT10FT <i>PowerCon Extension - 10 feet</i>	100.00
POWERCONEXT25FT <i>PowerCon Extension - 25 feet</i>	141.00
POWERCONEXT50FT <i>PowerCon Extension - 50 feet - bare wire lead</i>	191.00
4PXLREXT16IN <i>Unshielded 4-pin XLR Extension, 16in</i>	27.00
4PXLREXT5FT <i>Unshielded 4-pin XLR Extension, 5ft</i>	37.00
4PXLREXT50FT <i>Unshielded 4-pin XLR Extension, 15ft</i>	153.00
PCEXT0.5M <i>14 Gauge powerCON Extension 0.5m</i>	66.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclut pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siege Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

copyright © Jam Industries Ltd.



		Sugg. Retail Détail sugg.
PCEXT1.5M	14 Gauge powerCON Extension 0.5m	71.00
PCEXT3.0M	14 Gauge powerCON Extension 0.5m	80.00
PCEXT10.0M	14 Gauge powerCON Extension 0.5m	125.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclut pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

 Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com