

Video Panels

F4X4IP 4 panels included

Optical:

Light Source: 21,632 LEDs (tri-color RGB) SMD 1921, 50,000 hours life expectancy
Color Wavelength: red (619 to 624 nm), green (522 to 525 nm), blue (468 to 471 nm)

Viewing Angle: 140°

Illuminance: 5,500 NITS

Pixels: 104 x 208

Pixel Pitch: 4.8 mm

Pixel Density: 43,264/m²

Display Refresh Rate: 3,840 Hz

Construction:

Dimensions: 19.69 x 1.89 x 39.37 in (500 x 48 x 1000 mm)

Weight: 28.6 lb (12.88 kg)

Exterior Color: Black

Housing Material: Magnesium die-cast *Maximum vertical hang:* 16 panels

Maximum horizontal hang: 22 panels

Transparency: 0%



17,013.00

F3X4 4 panels included

Optical:

Light Source: 65,536 LEDs (tri-color RGB) SMD 2121, 50,000 hours life expectancy
Color Wavelength: red (619 to 624 nm), green (522 to 525 nm), blue (468 to 471 nm)

Viewing Angle: 140°

Illuminance: 1,200 NITS

Pixels: 128 x 256

Pixel Pitch: 3.9 mm

Pixel Density: 65,536/m²

Display Refresh Rate: 3,840 Hz

Construction:

Dimensions: 19.69 x 1.89 x 39.37 in (500 x 48 x 1000 mm)

Weight: 28.6 lb (12.88 kg)

Exterior Color: Black

Housing Material: Magnesium die-cast *Maximum vertical hang:* 16 panels

Maximum horizontal hang: 22 panels

Transparency: 0%



14,723.00

Rigging Bars

RB-F100CM *F-series™ Rig Bar is used to hang video panels vertically*
Works with CHAUVET® Professional F-Series Video Panels (F4)
Load Capacity: 650 lb (295 kg)
Fitted: M20 Eyebolt (5/8" shackle recommended)
Weight: 17.6 lb (5.2 kg)
Dimensions: 40.75 x 2.56 x 2.76 in (1,035 x 65 x 70 mm)



364.00

RB-F50CMX2 *F-series™ Rig Bars is used to hang video panels vertically or horizontally*
Works with CHAUVET® Professional F-Series Video Panels (F4)
Load Capacity: 650 lb (295 kg)
Eyebolts replaceable with preferred mounting hardware (such as 2 inch truss clamps)
Weight: 9.0 lb (4 kg) each
Dimensions: 21.07 x 2.56 x 2.76 in (535 x 65 x 70 mm) each



383.00

CT-APP *X-series™ Rig Bar is used to hang video panels vertically*
Works with CHAUVET® Professional X-Series video panels (PVP™ X3, PVP™ X6/P)
Load Capacity: 600 lb (272 kg)
Fitted: M20 Eyebolt (5/8" shackle recommended)
Weight: 11.4 lb (5.2 kg)
Dimensions: 23.15 x 5.12 x 6.46 in (588 x 130 x 164 mm)
Includes 1 x RB-XEBK



232.00

Accessories

MT-03 *Magnetic LED module replacement tool for the F4*



622.00

Arkaos Media Master *Media Server Software*

Express + KN

- Kling-Net support for easy plug-and-play configuration of EPIX™ and Nexus™ products
- Content DVD included (25 text layers, 26 Audio Visualizations, 169 source visuals)
- Support for SD & HD (includes AVI, MPEG, MPG, MOV, WMV, MP4, JPEG, GIF, BMP, PNG, SWF & more)
- Up to 4,096 user-configurable layers
- Easy to use interface



2,496.00

Arkaos Media Master *Media Server Software*

Express + KN+ 1 x ENTTEC DMX USB Pro

- Kling-Net support for easy plug-and-play configuration of EPIX™ and Nexus™ products
- Content DVD included (25 text layers, 26 Audio Visualizations, 169 source visuals)
- Support for SD & HD (includes AVI, MPEG, MPG, MOV, WMV, MP4, JPEG, GIF, BMP, PNG, SWF & more)
- Up to 4,096 user-configurable layers
- Easy to use interface
- Includes 1 x ENTTEC DMX USB Pro Mk2



2,874.00

VIPDRIV43S *All-in-one video wall mapper/scaler/switcher designed for use with Linsn video control protocol*

- Eliminates the need for individual mappers, scalers and video switchers
- Supports DVI, HDMI AND HD-SDI
- Includes 4 x Neutrik etherCON video outputs
- Capable of up to full HD at 2.6 million LEDs)



4,090.00

VIPDRIV43N *All-in-one video wall mapper/scaler/switcher designed for use with Novastar video control protocol*

- Eliminates the need for individual mappers, scalers and video switchers
- Supports DVI, HDMI AND HD-SDI
- Includes 4 x Neutrik etherCON video outputs
- Capable of up to full HD at 2.6 million LEDs)



5,726.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclut pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Cables

ETHERCONEXT18IN <i>Ethercon Extension - 18 inches</i>	41.00
ETHERCONEXT5FT <i>Ethercon Extension - 5 feet</i>	46.00
ETHERCONEXT10FT <i>Ethercon Extension - 10 feet</i>	70.00
ETHERCONEXT25FT <i>Ethercon Extension - 25 feet</i>	121.00
ETHERCONEXT50FT <i>Ethercon Extension - 50 feet</i>	171.00
POWERCONEXT18IN <i>PowerCon Extension - 18 Inches</i>	68.00
POWERCONEXT5FT <i>PowerCon Extension - 5 feet</i>	73.00
POWERCONEXT10FT <i>PowerCon Extension - 10 feet</i>	89.00
POWERCONEXT25FT <i>PowerCon Extension - 25 feet</i>	126.00
POWERCONEXT50FT <i>PowerCon Extension - 50 feet - bare wire lead</i>	170.00
4PXLREXT16IN <i>Unshielded 4-pin XLR Extension, 16in</i>	24.00
IP-4PXLREXT16IN <i>Unshielded IP-Rated 4-pin XLR Extension, 16in</i>	27.00
4PXLREXT5FT <i>Unshielded 4-pin XLR Extension, 5ft</i>	33.00
IP-4PXLREXT5FT <i>Unshielded IP-Rated 4-pin XLR Extension, 5ft</i>	38.00
4PXLREXT50FT <i>Unshielded 4-pin XLR Extension, 15ft</i>	136.00
IP-4PXLREXT50FT <i>Unshielded IP-Rated 4-pin XLR Extension, 15ft</i>	169.00
PCEXT0.5M <i>14 Gauge powerCON Extension 0.5m</i>	59.00
PCEXT1.5M <i>14 Gauge powerCON Extension 0.5m</i>	64.00
PCEXT3.0M <i>14 Gauge powerCON Extension 0.5m</i>	71.00
PCEXT10.0M <i>14 Gauge powerCON Extension 0.5m</i>	112.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclut pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com