

STRAIGHT SECTIONS

CT290-402S Length: 0.25 m (0.82 ft)
 Outer diameter tube: 2 in (50 mm)
 Dimensions: 11.42 x 11.42 in (290 x 290 mm)
 Wall thickness: 0.08 in (2 mm)
 Weight: 8 lbs (3.7 kg)
 Approvals: TUV, SLV




151.00

CT290-405S Length: 0.5 m (1.64 ft)
 Outer diameter tube: 2 in (50 mm)
 Dimensions: 11.42 x 11.42 in (290 x 290 mm)
 Diagonal bracing: 0.75 in (20 mm)
 Wall thickness: 0.08 in (2 mm)
 Weight: 11 lbs (5 kg)
 Approvals: TUV, SLV



283.00

CT290-407S Length: 0.75 m (1.64 ft)
 Outer diameter tube: 2 in (50 mm)
 Dimensions: 11.42 x 11.42 in (290 x 290 mm)
 Diagonal bracing: 0.75 in (20 mm)
 Wall thickness: 0.08 in (2 mm)
 Weight: 13.9 lbs (6.3 kg)
 Approvals: TUV, SLV



328.00

CT290-410S Length: 1 m (3.28 ft)
 Outer diameter tube: 2 in (50 mm)
 Dimensions: 11.42 x 11.42 in (290 x 290 mm)
 Diagonal bracing: 0.75 in (20 mm)
 Centerpoint load: 6,103 lbs (2,768 kg)
 Distributed load: 6,103 lbs (2,768 kg)
 Wall thickness: 0.08 in (2 mm)
 Weight: 15.87 lbs (7.2 kg)
 Approvals: TUV, SLV



369.00

CT290-415S Length: 1.5 m (4.92 ft)
 Outer diameter tube: 2 in (50 mm)
 Dimensions: 11.42 x 11.42 in (290 x 290 mm)
 Diagonal bracing: 0.75 in (20 mm)
 Wall thickness: 0.08 in (2 mm)
 Weight: 21.16 lbs (9.6 kg)
 Approvals: TUV, SLV



460.00

Confidential Dealer Price List / Liste de prix confidentielle

Sugg. Retail
Détail sugg.

CT290-420S Length: 2 m (6.56 ft)
Outer diameter tube: 2 in (50 mm)
Dimensions: 11.42 x 11.42 in (290 x 290 mm)
Diagonal bracing: 0.75 in (20 mm)
Centerpoint load: 4,568 lbs (2,072 kg)
Distributed load: 6,093 lbs (2,764 kg)
Wall thickness: 0.08 in (2 mm)
Weight: 26.45 lbs (12 kg)
Approvals: TUV, SLV



570.00

CT290-425S Length: 2.5 m (8.2 ft)
Outer diameter tube: 2 in (50 mm)
Dimensions: 11.42 x 11.42 in (290 x 290 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 33 lbs (15 kg)
Approvals: TUV, SLV



668.00

CT290-430S Length: 3 m (9.84 ft)
Outer diameter tube: 2 in (50 mm)
Dimensions: 11.42 x 11.42 in (290 x 290 mm)
Diagonal bracing: 0.75 in (20 mm)
Centerpoint load: 3,036 lbs (1,377 kg)
Distributed load: 6,075 lbs (2,756 kg)
Wall thickness: 0.08 in (2 mm)
Weight: 38.58 lbs (17.5 kg)
Approvals: TUV, SLV



753.00

ARC SECTIONS

CT290-415CIR180 Outside diameter: 4.92 ft (1.5 m)
Inside diameter: 3.28 ft (1 m)
Arc: 180°
Outer diameter tube: 2 in (50 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 21.6 lb (9.8 kg)
Approvals: SLV



1,151.00

CT290-420CIR90 Outside diameter: 6.56 ft (2 m)
Inside diameter: 4.92 ft (1.5 m)
Arc: 90°
Outer diameter tube: 2 in (50 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 25.8 lb (11.7 kg)
Approvals: SLV



822.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclus pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Confidential Dealer Price List / Liste de prix confidentielle

Sugg. Retail
Détail sugg.

CT290-430CIR90 *Outside diameter: 9.84 ft (3 m)*
Inside diameter: 8.20 ft (2.5 m)
Arc: 90°
Outer diameter tube: 2 in (50 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 28.6 lb (13 kg)
Approvals: SLV



1,065.00

CORNERS

CT290-490C *Length: 0.5 m (1.64 ft)*
Outer diameter tube: 2 in (50 mm)
Dimensions: 11.42 x 11.42 in (290 x 290 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 12.1 lbs (5.5 kg)
Approvals: SLV



459.00

CT290-4120C *Length: 0.5 m (1.64 ft)*
Outer diameter tube: 2 in (50 mm)
Dimensions: 11.42 x 11.42 in (290 x 290 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 12.12 lbs (5.5 kg)
Approvals: SLV



459.00

CT290-4135C *Length: 1.64 ft (0.5 m)*
Outer diameter tube: 2 in (50 mm)
Dimensions: 11.42 x 11.42 in (290 x 290 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 13.93 lbs (6.3 kg)
Approvals: SLV



459.00

CT290-43TC *Length: 1.64 ft (0.5 m)*
Outer diameter tube: 2 in (50 mm)
Dimensions: 11.42 x 11.42 in (290 x 290 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 14.33 lbs (6.5 kg)
Approvals: SLV



610.00

CT290-4390C *Length: 0.5 m (1.64 ft)*
Outer diameter tube: 2 in (50 mm)
Dimensions: 11.42 x 11.42 in (290 x 290 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 16.53 lbs (7.5 kg)
Approvals: SLV



610.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclut pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

copyright © Jam Industries Ltd.



Confidential Dealer Price List / Liste de prix confidentielle

Sugg. Retail
Détail sugg.

CT290-4VH *Adjustable range: 0° to 180°*
Plate thickness: 0.39 in (10mm)
Size: 11.42 x 11.42 in (290 x 290 mm)
Weight: 18.6 lbs (8.5kg)
Approvals: SLV



537.00

CT290-6WAYC *Outer diameter tube: 2 in (50 mm)*
Dimensions: 11.42 x 11.42 in (290 x 290 mm)
Diagonal bracing: 0.75 in (20 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 18.30 lbs (8.3 kg)
Approvals: SLV



603.00

BASE PLATES

CT290-4112B *12 inch base plate*
Thickness: 0.24in (6mm)
Dimensions: 12 x 12in (144 x 144mm)
Weight: 7.5 lbs (3.4 kg)



133.00

CT290-4116B *16 inch base plate*
Thickness: 0.24 in (6 mm)
Dimensions: 16 x 16 in (406 x 406 mm)
Weight: 9.0 lbs (4.1 kg)



231.00

CT290-4124B *24 inch base plate*
Thickness: 0.24 in (6 mm)
Dimensions: 24 x 24 in (610 x 610 mm)
Weight: 21.1 lbs (9.6 kg)



391.00

CT290-4130B *30 inch base plate*
Thickness: 0.24 in (6 mm)
Dimensions: 30 x 30 in (762 x 762 mm)
Weight: 31.70 lbs (14.4 kg)



428.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclut pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

copyright © Jam Industries Ltd. 

Confidential Dealer Price List / Liste de prix confidentielle

Sugg. Retail
Détail sugg.

ACCESSORIES

CT-APP Adjustable Panel Point for Video

The clamp mounting points are adjustable to work with box truss up to 20.5 wide.

The Adjustable Panel Point for Video provides a safe and secure connection and supports weights of up to 500 kg (1100 lb.)

Includes load rated 360-degree wrap around style coupler clamps made of heavy duty extruded aluminum that won't scratch or damage truss



328.00

CT-UTVM CT-UTVM is a universal, flat-screen TV mount designed to easily attach to the

TRUSST® trussing system and CHAUVET® DJ Heavy-Duty Tripod Stand (CH-01.)

Made of thick-gauge steel, this mount supports up to 200lbs and mounts TVs up to 50in. A built-in bubble level ensures everything is lined up for a perfect presentation every time.



233.00

CT-CONSPK Allows a loudspeaker to be mounted safely and securely on top of a totem

Includes adaptor and M10 mounting hardware

Made of lightweight aluminum

No tools required, for stress-free assembly



17.00

CT290-4105SK 105mm spacer

Manufactured from high-grade and lightweight aluminum

Spacer allows different style TRUSST® corners to mate together in certain configurations and circumstances

Extends the CT290-43TC to match the CT290-4390C and CT290-490C

Uses existing CT-CONKIT connecting hardware included with corners and sticks



92.00

CT290-4210SK 210 mm spacer

Manufactured from high-grade and lightweight aluminum

Spacer allows different style TRUSST® corners to mate together in certain configurations and circumstances

Extends the CT290-6WAYC to match the CT290-43TC, CT290-490C and CT290-4390C

Uses existing CT-CONKIT connecting hardware included with corners and sticks



170.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclus pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

copyright © Jam Industries Ltd.



page 5.

Confidential Dealer Price List / Liste de prix confidentielle

Sugg. Retail
Détail sugg.

CT-40110P

1 meter pipe
Length: 1 m (3.28 ft)
Outer diameter tube: 2 in (50 mm)
Wall thickness: 0.08 in (2 mm)
Weight: 3.5 lbs (1.58 kg)
Approvals: SLV



79.00

CT-CONKITB

CT-CONKIT-B is an additional set of conical connecting hardware for use with our TRUSST® Base Plates. Manufactured from high-grade and lightweight aluminum which is easy for transportation and setup. Compatible with the 12in, 16in, 24in and 30in base plates to create a stable and custom presentation. Includes 4 half-conical connectors, 4 spigots, 4 safety pins and 4 bolts to connect to TRUSST® base plates.



70.00

CT-CONKIT6WAY

CT-CONKIT6WAY is a set of connecting hardware that work with our TRUSST® 6-way Corner Block (each corner block includes two sets of connecting hardware at time of purchase). Manufactured from high-grade and lightweight aluminum which is easy for transportation and setup. Compatible with all TRUSST® sticks and the 6-way corner block to create an astonishing and custom presentation. Includes 4 half-conical connectors, 4 spigots, 4 safety pins and 4 bolts to connect to TRUSST® 6-way corner block.



61.00

CT-PIN12

CT-PIN12 is a connector that is compatible with all conical connectors and ensures a safe connection between our TUV-certified Truss pieces for overall design flexibility. Each set includes 12 spigots and 12 safety pins.



28.00

CT-CONKIT

CT-CONKIT is our most popular connecting hardware that safely connects all of our TUV-certified Truss pieces and most of our TRUSST® Corners together. Manufactured from high-grade and lightweight aluminum which is easy for transportation and setup. Compatible with all TRUSST® sticks to create an astonishing and custom presentation. Includes 4 conical connectors, 8 spigots and 8 safety pins to connect TRUSST® together.



73.00

CT290-DOLLYKIT

All-in-one kit includes dollies, truss spaces and ratchet straps. Fits the CT290 series and other major brands of 290mm square truss. Capacity: 12 straight truss sections, any length. Fits: 2 inch chord truss.



518.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclut pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

copyright © Jam Industries Ltd.



page 6.


TRUSS KITS

QTGOAL Portable goal post truss system designed to enhance any mobile set up at any size venue
 Quick and easy set up and tear down with pre-labeled connections and quick release pins
 Enhances durability and corrosion resistance with aluminum construction
 Holds up to 595lbs (270kg) (evenly distributed) when fully assembled
 Designed to fit CHAUVET® DJ MotionDrape™ LED
 Match any set up with selectable 5.5ft or 7.8ft height options
 Fits best in the CHAUVET® DJ CHS-Goal VIP Gear Bag
 Clamp that fits best with 35 mm truss is the CLP-35HC



1,762.00

QTARCH Portable arch truss system designed to enhance any mobile set up at any size venue
 Perfect lighting truss for venues with low ceilings • Quick and easy set up and tear down with pre-labeled connections and quick release pins
 Enhances durability and corrosion resistance with aluminum construction
 Holds up to 660lbs (300kg) when fully assembled—evenly distributed
 Fits best in the CHAUVET® DJ CHS-Arch VIP Gear Bag
 Clamp that fits best with 35 mm truss is the CLP-35HC



1,651.00

CHSQTG CHS-Goal VIP Gear Bags make it convenient and easy to transport the TRUSST® Goal Post Kit. Made from sturdy ballistic nylon, with heavy-duty handles and padded for extra protection, to safeguard your investment for years of worry-free use. Ideal for any entertainer looking for high mobility.



106.00

QT-CONICAL Manufactured from high-grade aluminum for durability and strength
 Compatible with Goal Post Kit conical couplers to safely assemble the kits
 Includes 4 conical connectors to replace lost or damaged hardware
 Only fits Goal Post Kit



68.00

QT-PIN12 Manufactured from high-grade steel for durability and strength
 Compatible with Goal Post Kit and Arch Kit conical couplers to safely assemble the kits
 Includes 12 spigots and 12 cotter pins to replace lost or damaged hardware
 Only fits Goal Post Kit and Arch Kit



68.00

QT-SNAP Manufactured from high-grade steel for durability and strength
 Compatible with Goal Post Kit and Arch Kit connectors to safely assemble the kits
 Includes 6 snap pins to replace lost or damaged hardware
 Only fits Goal Post Kit and Arch Kit










39.00

Confidential Dealer Price List / Liste de prix confidentielle

Sugg. Retail
Détail sugg.

CLAMPS, CABLES AND STANDS

CH05 <i>Steel cable ensures fixtures don't fall</i> 60lb	Load Capacity:		6.00
SC07 <i>Steel black aircraft cable ensures fixtures will not fall</i>	Load Capacity: 77.2lbs		10.00
CTC-S30 <i>Lightweight tripod stand geared towards production companies and mobile entertainers</i> Comes complete with T-bar adaptor All metal construction; no plastic parts to break for long-term durability Crank winch has built-in brake and a folding handle for safety and ease of use M12 threaded top hole 35mm top tube allows direct attachment of a speaker cabinet; no adaptor necessary Stand Height: 5.64 to 9.84 feet			350.00
CLP02 <i>Medium-duty c-clamp with adjustable knob fits on most fixtures</i> Made of steel for extra durability Load Capacity: 55lb Fits: 1 to 2 inch truss			7.00
CLP03 <i>Light-duty c-clamp with adjustable knob fits on most fixtures</i> Made of steel for extra durability Load Capacity: 44lb Fits: 1 to 2 inch truss			6.00
CLP05 <i>Heavy-duty c-clamp with adjustable knob fits on most fixtures</i> Made of cast iron for extra durability Load Capacity: 110lb Fits: 1 to 2.5 inch truss			21.00
CLP06 <i>Wraps completely around truss</i> Made of extruded aluminum Load Capacity: 220lb Fits: 2 inch			25.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclus pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

copyright © Jam Industries Ltd. 

Confidential Dealer Price List / Liste de prix confidentielle

Sugg. Retail
Détail sugg.

CLP10 Wraps completely around truss
Includes removable adaptors to fit different sizes of truss
Made of ABS plastic
Load Capacity: 75lb
Threaded Bolt: M10
Fits: 1in, 1.5in and 2in



15.00

CLP15 Wraps completely around truss
Made of aluminum
Load Capacity: 660lb
Threaded Bolt: M12
Fits: 2in



18.00

CLP15N Wraps completely around truss
Narrow design fits between cross braces with ease
Made of aluminum
Load Capacity: 330lb
Threaded Bolt: M12
Fits: 2in



20.00

CLP25N Wraps completely around truss
Swivels on its center to allow for complex rigging
Made of aluminum
Load Capacity: 880lb
Fits: 2in



37.00

CLP-35HC Wraps completely around 35mm truss for added security and stability
Made of aluminum
Load Capacity: 165lb
Fits: 1.3in



13.00

CTC-35SCX2 Allows you to attach the top of a tripod scrim securely and safely to the upright pole of any tripod stand
Made of high impact plastic, steel hinge pins, and steel tension bolt
The clamp fits any tripod stand from 1 3/8 in. up to 1 1/2 in. (35-38 mm) in diameter
Includes 2 clamps



17.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclus pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siege Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

copyright © Jam Industries Ltd. 

Confidential Dealer Price List / Liste de prix confidentielle

Sugg. Retail
Détail sugg.

CTC-50SC Swivel Coupler
 Load capacity: 1,650 lb (750 kg)
 Fits: 2 inch (50 mm) truss
 Weight: 2.8 lb (1.3 kg)
 Dimensions: 11.5 x 1.9 x 4.5 in (292 x 50 x 114 mm)



92.00

CTC-50SCL Swivel Coupler (lockable)
 Load capacity: 1,650 lb (750 kg)
 Fits: 2 inch (50 mm) truss
 Weight: 2.8 lb (1.3 kg)
 Dimensions: 11.5 x 1.9 x 4.5 in (292 x 50 x 114 mm)



92.00

CTC-50HC Full Size Half Coupler
 Threaded Bolt: M12
 Load capacity: 1,650 lb (750 kg)
 Fits: 2 inch (50 mm) truss
 Weight: 1.4 lb (0.6 kg)
 Dimensions: 5.75 x 1.9 x 4.5 in (146 x 50 x 114 mm)



48.00

CTC-50HCN Narrow Half Coupler
 Threaded Bolt: M12
 Load capacity: 1,650 lb (750 kg)
 Fits: 2 inch (50 mm) truss
 Weight: 1.0 lb (0.5 kg)
 Dimensions: 5.75 x 1.2 x 4.5 in (146 x 30 x 114 mm)



36.00

CT-50G Heavy Duty C-Clamp
 Completely anodized in black
 Threaded Bolt: M12 (also fits M10, not included)
 Load capacity: 550 lb (250 kg)
 Fits: 2 inch (50 mm) truss
 Weight: 1.0 lb (0.45 kg)
 Dimensions: 5.1 x 1.0 x 6.5 in (130 x 25 x 165 mm)



35.00

CTC-S60 Crank up Tower Stand
 Includes an adaptable T-Adaptor
 to 250 kg (550 lbs)
 brake Stand Height: 6.4 to 19.7 ft (1.95 to 6.0 m) *without T-bar adaptor
 Fits truss size: 12, 15, 16, 20.5 in (220, 290, 360, 390, 470 mm)

Supports up
 Safety locks and integrated winch
 brake



2,232.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclus pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

 Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

Confidential Dealer Price List / Liste de prix confidentielle

Sugg. Retail
Détail sugg.

CT-TENT *Clamps onto the slots on clear span tent Keder beam to suspend lighting, audio, truss, and décor elements.*
Tent clamp is made of zinc-plated steel, resists rust and corrosion.
Complete with welded eye bolt, makes attaching a load easy with standard rigging hardware.
Safe alternative to multi-piece handmade clamps.
Clamps to Keder beam by tightening one bolt, makes installation quick and easy.
Load Capacity: 330 lb (150kg)
Weight: 3.2 lb (1.5kg)



75.00

PRICES DO NOT INCLUDE GST AND ARE SUBJECT TO CHANGE WITHOUT NOTICE. "SUGGESTED RETAIL" ARE SUGGESTIONS ONLY. YOU ARE UNDER NO OBLIGATION TO ACCEPT THESE SUGGESTIONS AND YOU WILL IN NO WAY SUFFER IN OUR BUSINESS RELATIONS (OR IN YOUR RELATIONS WITH ANY OTHER PERSON) IF YOU FAIL TO ACCEPT THESE SUGGESTIONS. / Prix n'inclut pas la TPS et sont sujets à changement sans préavis. Les "prix suggérés" mentionnés ici ne sont que des suggestions. Vous êtes nullement obligé d'accepter ces suggestions et, si vous ne les acceptez pas, nos relations de travail n'en seront touchées d'aucune façon.

Orders / Commandes: 866-916-4660 • Fax: 888-918-2244

Service Phone: 877-JAMLINE or / ou 514-738-8155 • Service Fax: 1-800-563-2591

Head Office - Siège Sociale **Montreal** 21000 Trans-Canadienne • Baie D'Urfé, QC, H9X 4B7 • tel: (514) 457-2555 • fax: (514) 457-50055 • www.eriksonpro.com

copyright © Jam Industries Ltd. 